

	UBD814 TANDEM STRAIGHT BODY			UBD816 & UGD816 TANDEM MAX BODY		UPD1116 & UGD1116 TRIDEM STRAIGHT BODY			UPD1116 & UGD1116 TRIDEM MAX BODY	
	PERFORMANCE	PREMIUM	PLATINUM	PERFORMANCE	PREMIUM	PERFORMANCE	PREMIUM	PLATINUM	PERFORMANCE	PREMIUM
RELIABILITY - RATED CAPACITY										
GVWR (lb) – bumper pull/gooseneck	16,000			16,000/17,500		22,000			22,000	
Rated Payload (lb) – bumper pull/gooseneck for painted finish	10,800	10,600	10,550	10,400/11,350	10,050/10,850	15,950/15,400	15,750/15,150	15,700/15,100	15,900/15,300	15,550/15,150
Tongue Weight (lb) – bumper pull/gooseneck	2000			2000/3500		2200/4400			2200/4400	
Suspension	Torsion - Bolt On			Torsion - Bolt On		Equalized Leaf Spring			Equalized Leaf Spring	
Axle Rating (lb)	2 x 7000			2 x 7000		3 x 7000			3 x 7000	
DURABILITY - STRUCTURE										
HSS Mainframe Size (in)	8" x 3"			8" x 3"		8" x 3"			8" x 3"	
Bed Material	10 Gauge Steel			10 Gauge Steel		10 Gauge Steel			10 Gauge Steel	
Surface Finish	Polyurethane Primer & Paint			Polyurethane Primer & Paint or Galvanized		Polyurethane Primer & Paint			Polyurethane Primer & Paint or Galvanized	
Additional Premium Rockguard on Front Facing Surfaces		●	●		●		●	●		●
Side Height and Material – if applicable	18" - 10 Gauge Steel			21.75" - 10 Gauge Steel		18" - 10 Gauge Steel			21.75" - 10 Gauge Steel	
DIMENSIONS										
Total Length (ft) – bumper pull/gooseneck	20.3	20.9	20.4	22.3/25.4	22.8/26	22/25.4	22.6/26	22/25.4	22/25.4	22.6/26
Bed Length (ft)	14			16		16			16	
Bed Width (in) – floor/rim	82/82			82/97.2		82/82			82/97.2	
Bed/Floor Height (in) – unloaded/loaded	25.3/23			25.3/23		25.3/23			25.3/23	
INCLUDED EQUIPMENT										
Pull Type(s)	Bumper			Bumper or Gooseneck		Bumper or Gooseneck			Bumper or Gooseneck	
Jackleg Wind Type – top or side	Side			Side		Side			Side	
Jackleg Speeds	Dual			Dual		Dual			Dual	
Jackleg Lift Capacity (lb)	2 x 10,000			2 x 10,000		2 x 10,000			2 x 10,000	
Steel Tread Plate Fenders – bolt on	●			●		●			●	
Gate Type	2-Way	Combo	Hydraulic 2-Way	2-Way	Combo	2-Way	Combo	Hydraulic 2-Way	2-Way	Combo
Dump Hoist Cylinder	6" - 3200 psi - 15" Stroke			6" - 3200 psi - 20" Stroke		6" - 3200 psi - 20" Stroke			6" - 3200 psi - 20" Stroke	
HPU Type – P=power up/down, G=gravity down	P/G		P	P/G		P/G		P	P/G	
Black Steel Wheels	●	●		●		●	●		●	
Aluminum Spoke Wheels	○	○	●	○		○	○	●	○	
Wheel Size	16" Rim - 8 Stud - 6.5" Circle			16" Rim - 8 Stud - 6.5" Circle		16" Rim - 8 Stud - 6.5" Circle			16" Rim - 8 Stud - 6.5" Circle	
Tire Size	ST235/80R16 LRE			ST235/80R16 LRE		ST235/80R16 LRE			ST235/80R16 LRE	
Premium Radial 10 ply Tires – speed rated to 120 kph	●			●		●			●	
EASY TO OPERATE - SAFETY & CONVENIENCE FEATURES										
Dual Chains c/w hook latches – 36"	●			●		●			●	
Premium Protected Wiring	●			●		●			●	
4 x 4" D-Rings	●			●		●			●	
Breakaway Switch – includes LED test lights, battery & charger	●			●		●			●	
Tier 1 LED Lighting System	●			●		●			●	
Forward Self-Adjusting Brakes	●			●		●			●	
E-Z Lube Grease Axle Bearings	●			●		●			●	
110V Shore Charging Plug In	●			●		●			●	
Heavy Duty Toolbox	●			●		●			●	
Safety Prop Rod	●			●		●			●	
Bucket Shelf – Max Body™ models				●					●	
HD Charge Kit	○			○		○			○	
ADDITIONAL FEATURES										
Michels Premium Mesh Tarp	●			●		●			●	
Side Board Brackets	●					●				
Mud Flaps	○	○	●	○		○	○	●	○	
Spare Tire, Wheel, & Carrier	○	○	●	○		○	○	●	○	
ACCESSORIES										
Coupler Lock	○			○		○			○	
Wheel Locks	○			○		○			○	
Wireless Pump Remotes	○			○		○			○	
JD Link – fleet tracking	○			○		○			○	