



## **VRL800**

## **Auto Level Rotary Laser**

**Laser Beam:** Horizontal **Wave Length:** 635nm

**Operating Range:** 610m with Detector **Leveling Accuracy:** 1.6mm@30.5m h.

**Self Leveing Range:** ±5°

**Self Leveling Method:** Electronic Servo Motors

Bumper Sensor: On Board

Weight: 12lbs.

**Tripod Adaptor:**  $5/8 \times 11$  thread

## **3 Year Warranty**



#### **Exterior Package Includes:**

- VRL800 Rotary Laser
- Bracket and Remote Control
- Detector with Clamp
- Batteries and Charger
- Contractor's Tripod
- 9ft. Aluminum Rod
- Carry Case and Manual









# VRL800X

**Dial-in Grade Laser** 

Laser Beam: Horizontal & Zenith

Wave Length: 635nm

**Operating Range:** 610m with Detector **Leveling Accuracy:** 1.6mm@30.5m h.

3.2mm@30.5m v.

Self Leveling Method: Dial-in Automatic Programmable Grade Settings:  $\pm 8\%$ 

**Power:** Rechargeable Batteries **Tripod Adaptor:**  $5/8 \times 11$  thread

## 3 Year Warranty



#### **Exterior Package Includes:**

- VRL800X Rotary Laser
- Bracket and Remote Control
- Detector with Clamp
- Grid Target and Laser Glasses
- Rechargeable Batteries and Charger
- Contractor's Tripod
- 9ft. Aluminum Rod
- Carry Case and Manual



