

Road Warrior.

The Brandt **Work Ready**[™] Deckover Flatbed Trailers delivers superior capacity to get your equipment where it's going, every single day. This rugged model works as hard as you do, while taking all the punishment you can dish out.

1 Built to Last

Brandt trailers are purpose-built to maximize your productivity from dusk till dawn, until the job gets done:

- A Work Ready[™] frame built to reduce frame deflection under load, enhancing vehicle stability.
- Three available ramp configurations built to handle full equipment weight, enabling you to optimize your trailer for the task at hand.
- Reliable design and long-lasting components reduce total cost of ownership.

2 Easier to Operate

These trailers are designed for fast, effortless loading so you can start working sooner:

- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.
- Full-width ramps option accommodates any kind of equipment without hassle, ensuring superior versatility.
- 10,000 lb jacks are included as standard equipment to make coupling an uncoupling trailer effortless.

3 Safer

Safety is critical on the jobsite, so these models are designed with key features to maximize operator protection:

- Optional undercarriage toolbox, lower side step, and hydraulic ramps allow operators to work safely.
- Dependable axles ensure positive hitch weight distribution and overall stability when hauling concentrated heavy payloads.
- Fir decking provides a harder, longer lasting surface, capable of standing up to more abuse.



Powerful Value. Delivered.

DECKOVER FLATBED TRAILERS TECHNICAL SPECIFICATIONS

QUICK REFERENCE CHART	UGR1124 Deckover Flatbed		UPR1124 Deckover Flatbed		UGR1526 Tandem Dualies		UPR1628 Tridem/Tandem Dualies	
Base Unit Key Specifications	PERF		PERF		PERF	PLAT	PERF	PLAT
RELIABILITY - RATED CAPACITY								12/11
GVWR (lb)	22,000	25,000	22,000	23,000	30,000		32,000	
Rated Payload (Ib)	15,300	18,000	15,900	16,600	21,600	21,200	23,550	23,250
Suspension	10,000	10,000	.5,200		Leaf Spring	21,200	20,000	20,200
Axle Rating (Ib)	3 x 7000	2 x 10,000	3 x 7000	2 x 10,000		15,000	3 x 10,000	2 x 15,000
DURABILITY - STRUCTURE		.,		.,			,	
HSS Mainframe Size (in)		12" l-	Beam			14"	-Beam	
Premium Fir Decking	0		0		•		•	
Pressure-Treated Spruce/Pine Decking	0		0					
Polyurethane Primer & Paint		•		•	•		•	
Galvanized	0		0					
DIMENSIONS								
Total Length (ft)	38.4		35.1		40.5		39.6	
Fixed Deck Length (ft)	24		24		26		28	
Tail Length (ft)	5		5		5.1		5.1	
Deck Width (in) – inside fender to fender	102		102		102		102	
Deck Height (in)	35.5		35.4		39.5		38.5	
INCLUDED EQUIPMENT								
Hitch Type	Gooseneck		Bumper		Gooseneck		Bumper	
Jackleg Speeds	Single	Dual	Single	Dual	D	ual	Dual	Hydraulic
Jackleg Lift Capacity (lb)	2 x 1	0,000	2 x 1	0,000	2 x 1	0,000	2 x 10,000	1 x 10,000
Tire Size	ST235/80R16 LRE		ST235/80R16 LRE		ST215/75R17.5 LRH		ST235/ 80R16 LRE	ST215/ 75R17.5 LRH
Premium Radial Tires - speed rated to 120 kph	10 ply		10 ply		16 ply		10 ply	16 ply
Heavy Duty Toolbox	•		•		•			•
EASY TO OPERATE - SAFETY & CON	ENIENCE F	EATURES						
Spring Assist Beavertail Ramp - 24 x 60"	0		0					
Spring Assist Full Width Beavertail Ramp - 47 x 60"	0	•	0	•				
Spring Assist Full Width Beavertail Ramp - 44 x 68"					•		•	
Hydraulic Full Width Beavertail Ramp - 93 x 67"						•		•
Premium Protected Wiring	•							
Breakaway Switch – includes LED test lights, battery & charger	•							
Integral Footholds					•			
Underbody Toolbox						•		•
Tier 1 LED Lighting System					•			
Forward Self-Adjusting Brakes					•			
EZ-Lube Oil Bath Axle Bearings		•		•		•	(
EZ-Lube Grease Axle Bearings	•		•					
110V Shore Charging Plug In						•		0
Black (Silver for Dual) Steel Wheels					•			
HD Charge Kit						0		•
Mud Flaps	0		0			•	(
Chain Rack/Tray		•			0	•		
Spare Tire & Carrier		•		•	0	•	0	•

AVAILABLE ACCESSORIES: Locks for hitches