

LEAD
THE
FIELD.

15 Series Harvest GrainBelts



Belts Made Better.

Brandt Harvest GrainBelts gently move your crop with unmatched speeds to keep you one step ahead during harvest. The purpose-built A-Series 15" conveyors are available in lengths of 80', 90' and 100' to tackle all of your farming applications with ease.

① More Versatile

Three intake designs allow the unit to be optimized for any farm setup, maximizing performance when unloading trucks:

- The open-top standard intake delivers the proven performance that Brandt conveyors are known for.
- The high-capacity, low-profile intake on the LP+ field belt is now available for 15-Series Harvest GrainBelts so you can not only load bins, but unload too if extra reach is needed.
- The integrated swing away intake maintains optimal angles of operation at any raised height to maintain peak performance.

② More Productive

Brandt conveyors move up to 6,700 bu/hr, saving you time and money:

- Innovative S-drive technology delivers 270° of wrap for increased traction and consistent performance.
- Brandt's EZTRAK tensioning and tracking system keeps your belt aligned with the patented steel envelopes and properly tensioned with heavy-duty springs. The visual tension indicator makes it easy to see when adjustment is needed.
- Effortlessly move your swing hopper with the LeadHand mobile app or by remote control using the EZSWING mover system to achieve maximum productivity.

③ More Durable

Brandt's harvest grain belts are purpose-built to minimize wear and tear and ensure a long working life:

- The 35" belt take-up delivers improved tensioning while all rollers are replaceable without removing the belt, eliminating the need for spring re-tensioning.
- Welded wind guards deliver maximum tube strength and protection from the elements while removable panels on the underside ensure easy belt access.
- Brandt's scissor-lift undercarriage delivers unmatched strength and rigidity, ensuring smooth operation and maximum reach into any bin.

Powerful Value. **Delivered.**

Brandt

HARVEST GRAINBELTS

SPECIFICATIONS

	1580A	1590A	15100A
Performance			
Capacity (bushels per hour)	6,200 - 6,700	6,200 - 6,700	6,200 - 6,700
Horsepower Requirement – PTO / Gas / Elec	55 / 35 / 15	55 / 38 / 20	55 / 40 / 25
Dimensions			
Belt Width	15"	15"	15"
Conveyor Length	80'	90'	100'
Raised Height	38' 9" - 39' 4"	43' 9" - 44' 5"	48' 9" - 49' 5"
Raised Reach	31' 3"	39' 2"	42' 6"
Lowered Reach	36' 11"	46' 3"	51' 2"
Transport Height	12' 11"	13' 6"	13' 6"
Transport Length	84' 11"	94' 11"	104' 11"
Wheel Track Width	12' 2"	12' 2"	12' 2"
Total Weight (lb)	5,809 - 6,228	6,051 - 6,489	6,434 - 6,710
Tube Diameter	10"	10"	10"
Tire Size	225/75R15	225/75R15	225/75R15
Features			
Hydraulic Winch	Optional	Optional	Optional
Windguards	Standard	Standard	Standard
Belt Type	2-Ply Rubber	2-Ply Rubber	2-Ply Rubber
Drive System	S-Drive	S-Drive	S-Drive
Hopper			
Hopper Style	Low Profile	Low Profile	Low Profile
Hopper Width and Length	36" x 70"	36" x 70"	36" x 70"
Collapsed Hopper Height	16"	16"	16"
Extended Hopper Height	16"	16"	16"

OPTIONS

Auger steer

Bucket spout

Hopper cover

Hydraulic brake winch

Safety lights

Work lights

Electric clutch*

Remote clutch*

Soft-start clutch*

EZMOVE*

* Standard and LP intake only

For more information
Call us at 1-866-4-BRANDT
Email us at agriculture@brandt.ca
Or visit us at www.brandt.ca

Brandt Agricultural Products
PO Box 317, 13th Avenue & Pinkie Road,
Regina, SK, Canada
S4P 3A1

