MADE FOR MORE TO KEEP PACE WITH YOU

The **Eeger Beever 1621X Brush Chipper** is the scaled down version of the Eeger Beever 1821 Chipper featuring reduced horsepower engine selections and spring applied down pressure. This powerful, high performing chipper provides a balance between performance, production, capability and efficiency - making it the ideal unit for residential tree services, utility line clearing, vegetation management, maintenance contractors, municipalities and more.

MORBARK

FEATURES AND BENEFITS

- Equipped with a wide infeed opening, dual feed wheels, spring applied down pressure, and straight flow-through design, the feed system easily climbs over material, reducing drag and increasing chipping efficiency
- Bearing style feed wheel pivot assembly contours the radius of the drum, reducing dead space between the feed wheel and drum and creates a mechanical advantage for increased down pressure.
- Powerful TorqMax[™] top feed wheel drive system amplifies material pulling power for the most demanding applications
- Direct drive bottom feed wheel with clean-out door is speed matched to the top feed wheel to provide continuous material flow
- Large diameter chipping drum with staggered knife pockets maintains chipping power while providing consistent chip quality
- Four dual-edged chipper knives with replaceable knife holders allows ease of chipper drum maintenance and allows the drum to be rebuilt versus replaced, reducing expenses





1621 BRUSH CHIPPER SPECIFICATIONS

Specifications may vary with equipment options

Updated 9/23/2022

GENERAL	US	METRIC
Height	8'8"	2.64 m
Width	7'4"	2.24 m
Length	18'8"	5.69 m
Gross weight (approximate)	8,900 - 10,200 lb	4,037 - 4,627 kg
Suspension	10,000 lb Torsion	4,336 kg Torsion
Infeed opening (height x width)	41" x 59"	104.1 x 149.9 cm
Throat opening (height x width)	18" x 20.5"	45.72 x 52.1 cm
Drum (width x diameter)	23.8" x 21.4"	60.45 x 76.2 cm
Engine		John Deere or PSI
Horsepower	140–145 HP	104.4–108.1 kW
Fuel capacity	32 gallons	121.1 L
Hydraulic capacity	12 gallons	45.2 L
Frame	8.2 lb, 6" channel	3.7 kg, 15.2 cm channel
Tires		(2) 245/70Rx17.5
Hitch	2.5" Pintle	6.4 cm Pintle

EQUIPMENT HIGHLIGHTS

- Choice of gasoline, or diesel engine packages
- Bearing style feed wheel pivot assembly
- Staggered knife pocket drum with four dual-edged chipper knives and replaceable knife holders
- Dual sided air-impeller system increases chip velocity, aiding in discharging wet, leafy and fibrous material
- Feed wheels equipped with serrated teeth and knife bar combination for continuous material flow
- Reversing automatic feed system stops and momentarily backs away material for increased feeding efficiency and guicker engine recovery
- Standard fuel sight gauge, drain plug and shut-off valve
- Standard hydraulic reservoir clean-out/inspection cover, magnetic drain plug and fluid level sight gauge
- Fully extended channel steel frame fully supports the entire chassis

OPTIONS INCLUDE

- Winch Package
- Bottom Bump Bar
- Variable Speed Flow Control
- Chocks and chock holder
 Traffic cone holder
- Traffic cone holder

