

LEAD
THE
FIELD.

EZReach Swing Away Auger



Full Speed Ahead.

Move your crop, not your trailer with the all-new, fastest-ever EZReach from Brandt. This unit has been redesigned with a 25% larger hopper to speed up your operation. And, the optional electric controls integrate with the Brandt LeadHand™ app for full remote control of the swing hopper — an industry-first.

① Industry-Leading Performance

Keep your trucks moving with easy unloading and maximum throughput:

- Designed for unmatched cleanout.
- Tapered hopper corners improve the flow of grain into the transition.
- Topside grain seal on the transition pivot point reduces grain leakage.

② Fast Positioning

The EZReach is purpose-built for quick positioning during your fast-paced harvest:

- Optional electric-over-hydraulic controls integrate with the Brandt LeadHand™ app for full remote control of swing hopper placement.
- The increased catchment area of the hopper provides an easy-to-hit unloading target.
- Three-way controls allow for easy operation and precise hopper placement.

③ Maximum Uptime

There's no time for downtime on a busy farm, so these units are built to last:

- Easy-to-remove service component panels make maintenance fast and easy.
- Durable hopper design maximizes integrity.
- Superior powder coat paint optimizes cleanout, rust protection, component life, and resale value.

Powerful Value. **Delivered.**

Brandt

EZREACH SWING AWAY AUGER

SPECIFICATIONS

	13HP+ EZReach	16HP EZReach
Swing Tube		
Stroke	9'	9'
Working Retraction	24"	24"
Booster Flight Thickness	1/4"	1/4"
Swing Tube Flight Thickness	3/16"	3/16"
Core Diameter	3" OD	4" OD
Swing Tube Thickness	12 Gauge	10 Gauge
Transition Flight Thickness	5/16"	1/4"
Tube Length	17'	17'
Power Extend	Yes	Yes
Mechanical Drive	Yes	Yes
Hopper		
Hopper Design	Low Profile	Low Profile
Hopper Height (w/o rubber extension)	12 1/2"	12 1/2"
Power Swing	Yes	Yes
Power Tilt	Yes	Yes
Hopper Wheels	10" Solid	10" Solid
Drive Wheels	Pneumatic 16" Lug	Pneumatic 16" Lug
Hopper Flighting Gauge	3/8"	3/8"
Flighting Diameter	6 3/4"	7 1/8"
Core Diameter	1 1/4" OD	1 1/2" OD
Number of Support Wheels	4	4

FEATURES

17' Swing Tube

Features a 9' stroke to ensure that your trailer hoppers are always within reach.

14" Diameter Swing Tube

On the 13HP+ delivers high-capacity to ensure maximum grain flow into the auger.

Three-way Hydraulic Controls

For easy operation and precise hopper placement.

Abrasion-resistant Paint

Maximizes lifecycle and resale value with the industry's most durable powder-coat finish.



Brandt LeadHand™ app



For more information
Call us at 1-866-4-BRANDT
Email us at agriculture@brandt.ca
Or visit us at www.brandt.ca

Brandt Agricultural Products
PO Box 317, 13th Avenue & Pinkie Road,
Regina, SK, Canada
S4P 3A1

