

# Safety Data Sheet

## Synthetic Engine Oil 0W-40

### **1. PRODUCT AND COMPANY IDENTIFICATION**

Product Name	:	Synthetic Engine Oil 0W-40
Supplier	:	ValPar PO Box 3856, Hwy #1 East Regina, SK S4P 3R8 CANADA
Telephone	:	877-685-4886
Product/MSDS Information	:	306-791-5911
Canutec (24 hr)	:	613-996-6666



## 2. COMPOSITION/INFORMATION ON INGREDIENTS

OSHA Hazardous Components (29 CFR 1910.1200) 1-Decene, Momopolymer, Hydrogenated Base, CAS#Mixture Zinc And Zinc Compounds, CAS#Mixture See Section 8 For Exposure Limits\*

### **3. HAZARDS IDENTIFICATION**

Potential Health Effects : Minor Eye, Inhalation And Skin Irritant.

\*See Section 11 For Toxicological Information\*

### **4. FIRST AID MEASURES**

Еуе	:	Flush with water for 15-20 minutes. Seek medical attention if irritation develops.
Skin	:	Wash immediately with soap and water. Remove contaminated clothing and launder before reuse. Discard shoes and leather articles saturated with the product. Obtain medical advice if irritation occurs.
Inhalation	:	Remove exposed person to fresh air. If breathing is labored give oxygen. If breathing has stopped apply artificial respiration. Get immediate medical attention.
Ingestion	:	Do not induce vomiting. If conscious, give 2 glasses of water. If vomiting does occur, keep head below the hips to reduce risk of aspiration. Get immediate medical attention.



### **5. FIRE FIGHTING MEASURES**

<b>Flammability Properties</b>
--------------------------------

Flash Point
Method
LFL/UFL
Auto-Ignition Temperature
Extinguishing Media
Firefighting Equipment

:	Not Determined

COC. ASTM D-92

224°C

:

- : Not Determined
- : Carbon Dioxide, dry chemical, and alcohol foam.
- : Full bunker gear recommended including a positive pressure self-contained breathing apparatus.

### 6. ACCIDENTAL RELEASE MEASURES

Isolate spill area. Provide adequate ventilation. Wear appropriate personal protection. Recover free product for recycle an /or disposal. Add sand, earth or other suitable absorbent to spill area. Prevent entry into sewers and waterways. Check under Transportation and Labelling (DOT/CERCLA) and Other Regulator Information Section (SARA) for hazardous substances to determine regulatory reporting requirements for spill.

#### 7. HANDLING & STORAGE

Handling	:	Keep containers closed. Avoid contact with eyes, skin or clothing. Wash hands after handling. Empty container may retain product residue which may exhibit hazards of product.
Storage	:	Keep away from heat or flame.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation	:	Use adequate general or local exhaust ventilation to keep airborne concen- trations below exposure limits.
Respiratory	:	Use a NIOSH approved respirator when necessary.
Skin	:	Use Viton or Nitrile gloves to avoid prolonged or repeated skin contact.
Еуе	:	Use splash goggles or face shield where splashing is expected or can occur
Exposure Limits	:	The Threshold Limit Value (TLV) OF 5 mg/m3 is suggested for oil mist.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	:	Liquid
Vapor Density (Air=1)	:	Negligible
Solubility in Water	:	Negligible
Specific Gravity	:	0.8660
Volatility (Volume)	:	Negligible
рН	:	Essentially Neutral



Odor	:	Mild, Bland, Hydrocarbon Odor
Appearance	:	Amber Transparent Colored Liquid
Viscosity, cST @ 100°C	:	13.5
Viscosity, cST @ 40°C	:	65
Viscosity Index	:	180
Refractive Index	:	1.4664
Fire Point	:	238°C
Pour point	:	-45°C
4-Ball Para 1	:	0.38
4-Ball Para 3	:	0.55

## 10. STABILITY AND REACIVITY

Stability Incompatibility Hazardous Polymerization	:	Stable under moderately elevated temperatures and pressures. Avoid contact with strong oxidants. Will not occur.
Hazardous Decomposition of Product	:	Toxic oxides of carbon, aldehydes and other products of complete combus- tion.

## **11. TOXICOLOGICAL INFORMATION**

#### Acute Exposure

Eye	:	Moderate to strong eye irritation. Based on data from components or similar material.
Skin Irritation	:	Not expected to be a primary skin irritant. Based on data from components or similar material. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying, defatting, and cracking of the skin.
Respiratory Irritation	:	If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract similar to that observed with mineral oil. Based on data from components or similar materials. Under good industrial hygiene practices where all exposure limits are observed, respiratory irritation should not be a problem
Chronic Exposure		
Chronic Toxicity	:	No data available to indicate product present at greater than 1.0% are chronic health hazards.
Carcinogenicity	:	No data available to indicate product present at greater than 0.1% are a carcinogenic hazard.
Mutagenicity	:	No data available to indicate product present at greater than 1.0% present a mutagenic or genotoxic hazard.
Reproductive Toxicity	:	No data available to indicate product present at greater than 1.0% present a reproductive hazard.
Teratogenicity	:	No data available to indicate product present at greater than 1.0% present a teratogenic hazards.



#### Additional Information

**Exposure Limits** 

: Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter.

### **12. ECOLOGICAL INFORMATION**

No data available on the adverse effects of this product on the environment.

#### **13. DISPOSAL CONSIDERATIONS**

If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

### **14. TRANSPORT INFORMATION**

This product is not classified as hazardous material for DOT SHIPPING. For further information relative to spills resulting from transportation incidents, refer to the latest DOT Emergency Response Guidebook for Hazardous Materials.

#### **15. REGULATORY INFORMATION**

#### U.S. Federal Regulations

OSHA TABLE Z TSCA CERCLA 40 CFR 302.4 <u>SARA Title III</u>	:	Synthetic Base Stock (Mist) Not Applicable Zinc Compounds @ 1.30-2.58% RQ 1 lb
Section 302 Extremely		
Hazardous	:	Not Applicable
Section 311/312	:	Fire Hazard: Yes Reactive Hazard: No Release of Pressure: No Acute Health Hazard: Yes Chronic Health Hazard: No
Section 313		
Toxic Chemical	:	Not Applicable
U.S. State Regulations		
California (PROP 65)	:	Does not contain chemicals known to the state of California to cause cancer.
International Regulations		
WHMIS	:	All components listed.



Product Name:Synethic Engine Oil 0W-40Revision Date:August 20, 2018Page:5 of 5

### **16. OTHER INFORMATION**

The information contained herein is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury or third person proximately caused by the material if reasonable safety measures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third person proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumed the risk in his use of the material.