

LEAD  
THE  
FIELD.

## 20 & 24 Series Harvest GrainBelts



### Belts Made Better.

Introducing the all-new 24-Series and the redesigned 20-Series Harvest GrainBelts from Brandt. These belts are the fastest, the easiest-to-use, and offer the longest reach in the industry. And, they deliver the strength and reliability that gets you through the toughest harvest.

#### ① Productivity

Brandt GrainBelts boost your productivity with high performance and ease-of-use:

- Low-profile technology and shallow angles in all working positions boosts throughput.
- 24-Series models move up to 14,000 bu/hr.
- The full range delivers industry-leading reach, including the new 125' model.

#### ② Unrivalled Uptime

You can count on the 20- and 24-Series GrainBelts to deliver uninterrupted harvest efficiency:

- The new hydraulic hoist simplifies transport while increasing balance and stability.
- Patented EZTRAK system shows at a quick glance whether the belt needs more or less tension.
- All-new S-Drive system maximizes belt engagement with a 13.5" drive roller and 290° of belt wrap.

#### ③ Low Operating Cost

The 20- and 24-Series are built for long-lasting performance, ensuring the best possible resale value:

- Redesigned undercarriage, strengthened tube, and solid truss add stability to extend product life.
- Fixed swing-away intake with electric EZSWING mover provides fast, efficient truck unloading.
- Proprietary sealing components ensure minimum leakage.

Powerful Value. **Delivered.**

**Brandt**

# HARVEST GRAINBELTS

## SPECIFICATIONS

	2021A LP	2095A	20110A	20125A	2421A LP	2495A	24110A	24125A
<b>Performance</b>								
Capacity	Up to 12,000 bu/hr				Up to 14,000 bu/hr			
HP Requirement – PTO / Elec	-	80 / 40	100 / 50	120 / 50	-	90 / 40	110 / 50	130 / 50
<b>Dimensions</b>								
Belt Width	20"	20"	20"	20"	24"	24"	24"	24"
Conveyor Length	21'	95'	110'	125'	21'	95'	110'	125'
Raised Height	55"	50'	56' 11"	65' 1/2"	55"	50'	56' 11"	65' 1/2"
Raised Reach	100"	45' 3"	44' 9"	57' 9"	100"	45' 3"	44' 9"	57' 9"
Lowered Reach	101"	51' 1"	50' 8"	65' 7 1/2"	101"	51' 1"	50' 8"	65' 7 1/2"
Transport Height	77"	13' 7"	15' 1/2"	16' 1/2"	77"	13' 7"	15' 1/2"	16' 1/2"
Transport Length	23' 9"	98' 3 1/2"	113' 7"	128' 6"	23' 9"	98' 3 1/2"	113' 7"	128' 6"
Wheel Track Width	66"	13"	13' 4"	13' 4"	66"	13"	13' 4"	13' 4"
Total Weight (lb)	1,418	11,686	12,692	13,437	1,574	13,553	14,572	15,317
Tube Size	14"	14"	14"	14"	14"	14"	14"	14"
Tire Size	ST205/75R15	ST235/85R16	IF320/70R15	IF320/70R15	ST205/75R15	ST235/85R16	IF320/70R15	IF320/70R15
Hydraulic Cylinder Size (Bore x Stroke)	N/A	4 1/2" x 29 3/4"	5" x 36"	5" x 36"	N/A	4 1/2" x 29 3/4"	5" x 36"	5" x 36"
<b>Features</b>								
Lift Mechanism	N/A	Scissor Lift (single acting)			N/A	Scissor Lift (single acting)		
Windguards	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Belt Type	Rubber	Rubber	Rubber	Rubber	Rubber	Rubber	Rubber	Rubber
Drive System	Top Drive	S-Drive	S-Drive	S-Drive	Top Drive	S-Drive	S-Drive	S-Drive
Swing Drive System	N/A	Elec or Hyd	Elec or Hyd	Elec or Hyd	N/A	Elec or Hyd	Elec or Hyd	Elec or Hyd
<b>Low Profile Hopper</b>								
Hopper Dimensions (L x H)	72" x 40"	72" x 40"	72" x 40"	72" x 40"	72" x 40"	72" x 40"	72" x 40"	72" x 40"
Hopper Height (lowered)	10"	10"	10"	10"	10"	10"	10"	10"
Hopper Height (raised)	18"	18"	18"	18"	18"	18"	18"	18"

## FEATURES

### Integrated Swing-Away Intake

Positioned for maximum clearance, reach, and capacity.

### Transport Hoist

Optimizes transport position by using a hydraulic hoist instead of a winch.

### Solid Wind Guards & Reinforced Tube

Adds structural strength.

### Standard Solid Truss

Improves structural strength and performance over cable systems.

### 13.5" Drive Roller

Simplifies the S-Drive for increased reliability and easy maintenance.

### Hydraulically-controlled Hitch

Quickly adjusts between transport and working positions, eliminating the need for a jack.

### Options to Fit Your Needs

Including LED work and safety light kits, hydraulic steering kit, pivot axle kit for bunker piling, and capacity-matching transfer belts.

For more information  
Call us at 1-866-4-BRANDT  
Email us at [agriculture@brandt.ca](mailto:agriculture@brandt.ca)  
Or visit us at [www.brandt.ca](http://www.brandt.ca)

**Brandt Agricultural Products**  
PO Box 317, 13th Avenue & Pinkie Road,  
Regina, SK, Canada  
S4P 3A1

