

LEAD
THE
FIELD.



Oilseed-Certified™ Field GrainBelts

2 YEAR EXTENDED WARRANTY

To ensure that your equipment is always ready to work when you need it, Brandt backs its products with a two-year limited warranty. *Ask us for details.*



One Belt Fits All.

Load all of your crops – even canola – with the all-new Oilseed-Certified™ GrainBelt from Brandt. This belt is the first-ever to be designed specifically for oilseed. And, it is backed up by warranty that is not limited by use in oilseed crops.

① Purpose-built

Move your oilseed with confidence using Brandt's specially-designed belt:

- Industry-unique rubber belt will not degrade from handling oilseed.
- V-shape belt pattern with raised edges centres product on the belt.
- Manufacturer warranty is not limited by use in oilseed production, an industry first.

② Product Retention

New design protects your equipment and your crop by preventing leakage:

- Gentle conveying saves your crop from the damage associated with conventional augers.
- Fortified sealing throughout the transition and intake keep your product on the belt.
- Specialized sealing at critical points dramatically reduces leakage compared to standard conveyors.

③ Effortless Cleanout

Minimize manual cleanout with the Oilseed-Certified™ GrainBelts' self-cleaning system:

- The belt is cleaned at critical points to virtually eliminate crushed oilseed build-up.
- Roller guarding and cleanout ports clear the backside of the belt.
- Removable tray under the S-drive enables easy clean out of the drive rollers and protects the engine.

Powerful Value. **Delivered.**

Brandt

OILSEED-CERTIFIED™ FIELD GRAINBELTS

SPECIFICATIONS

	1547LP+	1552LP+	2045LP+	2055LP+
Performance				
Capacity (bushels per hour)	up to 9,000	up to 9,000	up to 12,000	up to 12,000
Recommended Horsepower - Gas	35	35	35	35
Dimensions				
Belt Width	15"	15"	20"	20"
Conveyor Length	47'	52'	47' 11"	55'
Raised Height	22' 9"	24' 8"	21' 3"	25' 5"
with EZMOVE	22' 8"	-	-	-
Raised Reach	20' 10"	23' 6"	17' 3"	22' 10"
Lowered Reach	23' 2"	26'	19' 7"	24' 6"
Transport Height (hitch at 12")	12' 2"	13' 5"	11' 7"	12' 8"
Transport Length	49' 8"	56' 3"	50' 9"	60' 5"
Intake Reach	15' 6"	15' 6"	24' 2"	15' 2"
with EZMOVE	15' 4"	14' 7"	16'	15' 2"
Wheel Track Width	94"	94"	94"	130"
Total Weight	2,350 lb	2,590 lb	4,950 lb	6,700 lb
Hitch Weight (without EZMOVE)	320 lb	300 lb	200 lb	450 lb
Tube Diameter	10"	10"	14"	14"
Tire Size	ST205/75D15	ST205/75D15	ST225/75R15	ST225/75R15
Features				
Hydraulic Winch	Optional	Optional	Optional	Optional
Windguards	Standard	Standard	Standard	Standard
Belt Type	Oilseed-Certified™	Oilseed-Certified™	Oilseed-Certified™	Oilseed-Certified™
Drive System	S-Drive	S-Drive	S-Drive	S-Drive
Hopper				
Hopper Style	Low Profile	Low Profile	Low Profile	Low Profile
Hopper Width and Length	36" x 70"	36" x 70"	40" x 70"	40" x 70"
Collapsed Hopper Height	7.5"	7.5"	9.5"	9.5"
Extended Hopper Height	14"	14"	16"	16"

FEATURES

Upgraded LP+ Field GrainBelt Chassis

Delivers a proven track record of success.

Low-profile Hopper

Easily fits at only 7.5" high collapsed and 14" extended.

EZTRAK Tensioning and Tracking System

Ensures belt is aligned and tensioned.

Standard EZMOVE

The joystick controlled power steering delivers improved control with less effort.

Optional All-wheel Drive EZMOVE

Allows the operator to effortlessly move 15 Series GrainBelts anywhere with dramatically improved all-terrain performance.

For more information
Call us at 1-866-4-BRANDT
Email us at agriculture@brandt.ca
Or visit us at www.brandt.ca

Brandt Agricultural Products
PO Box 317, 13th Avenue & Pinkie Road
Regina, SK, Canada
S4P 3A1

