

**LEAD
THE
FIELD.**

S-Drive Field GrainBelts



Gentle Handling. Maximum Performance.

Brandt's 15LP+ and 20LP S-Drive Field GrainBelts allow you to move large quantities of grain quickly and gently. Whether it's from a truck to an air cart or from a storage system to a transport truck, Brandt conveyors handle the job with ease. And, they're purpose-built to protect your seed investment and maintain grain quality, all while moving up to 12,000 bu/hr.

① Performance Boost

Get better performance with gentle handling:

- The optimized intake and transition increases grain-flow efficiency to achieve peak performance in varying conditions.
- The S-Drive design provides over 290° of belt wrap to maximize contact with the drive roller, increasing traction for improved performance and less belt wear.
- Over 34" of available belt take up ensures proper belt tensioning in all conditions.

② Maximum Versatility

Achieve ultimate product retention with these versatile machines:

- The double lip intake seal keeps your crop on the belt where it belongs, increasing product retention while loading.
- Lowest clearance intake hoppers (7.5") with retractable hopper fabric that extends up 16".
- Available Oilseed-Certified™ models load all of your crops safely with an industry-exclusive oil-resistant belt.

③ Easy To Operate

The user-friendly design promotes increased operator safety and productivity:

- Brandt's EZTRAK tensioning and tracking system keeps your belt aligned and properly tensioned at all times. And, the visual tension indicator makes it easy to see when adjustment is needed.
- The enclosed drive system and wind guards deliver environmental protection and operator safety.
- The frame-integrated EZMOVE provides a compact design for increased intake reach and features a joystick control and hydraulic winch to ensure safe, easy operation.

Powerful Value. **Delivered.**

Brandt

S-DRIVE FIELD GRAINBELTS

SPECIFICATIONS

	1537LP+	1547LP+	1552LP+	2045LP	2055LP
Performance					
Capacity (bushels per hour)	up to 9,000	up to 9,000	up to 9,000	up to 12,000	up to 12,000
Recommended Horsepower - Gas	35	35	35	35	35
Dimensions					
Belt Width	15"	15"	15"	20"	20"
Conveyor Length	37'	47'	52'	45'	55'
Raised Height	17' 10"	22' 8"	24' 8"	21' 3"	25' 5"
Raised Reach	15' 4"	20' 10"	23' 6"	17' 3"	22' 10"
Lowered Reach	16' 7"	23' 2"	26'	19' 7"	24' 6"
Transport Height (hitch at 12")	11' 5"	12' 2"	13' 5"	11' 7"	12' 8"
Transport Length	39' 8"	49' 8"	56' 3"	50' 9"	60' 5"
Intake Reach	12' 2"	15' 4"	14' 7"	16'	15' 2"
Wheel Track Width	94"	94"	94"	94"	130"
Total Weight	1,945 lb	2,350 lb	2,590 lb	4,950 lb	6,700 lb
Tube Diameter	10"	10"	10"	14"	14"
Tire Size	ST205/75D15	ST205/75D15	ST205/75D15	ST225/75R15	ST225/75R15
Features					
Hydraulic Winch	Optional	Optional	Optional	Optional	Optional
Windguards	Standard	Standard	Standard	Standard	Standard
Drive System	S-Drive	S-Drive	S-Drive	S-Drive	S-Drive
Hopper					
Hopper Style	Low Profile	Low Profile	Low Profile	Low Profile	Low Profile
Hopper Width and Length	36" x 70"	36" x 70"	36" x 70"	40" x 70"	40" x 70"
Collapsed Hopper Height	7.5"	7.5"	7.5"	9.5"	9.5"
Extended Hopper Height	14"	14"	14"	16"	16"

OPTIONS

All-wheel Drive EZMOVE

Allows you to move Brandt grain belts anywhere with dramatically improved all-terrain performance.

Electric clutch with soft-start module

Allows you to engage the belt smoothly, reducing shock on the drive system and increasing product longevity.

Work-light Kit

Provides complete visibility when loading trucks at night.

For more information
Call us at 1-866-4-BRANDT
Email us at agriculture@brandt.ca
Or visit us at www.brandt.ca

Brandt Agricultural Products
PO Box 317, 13th Avenue & Pinkie Road
Regina, SK, Canada
S4P 3A1

