



UBT2524

# 24' TAG TRAILER TILT DECK



INDUSTRY BEST WARRANTY

## 5 YEAR WARRANTY

2 Year Bumper-To-Bumper and 5 Year Structural warranty make ownership stress-free. Ask us for details.

## Productivity Powerhouse.

Introducing the 25-ton Tag Along Tilt Deck Trailer from Brandt. This trailer delivers an impressive 49,850 lb of payload capacity, 8.5' wide deck, and a total length of 38' consisting of a 24' tilt deck and 6' dovetail. With fast, effortless loading and long-lasting components, this is a trailer you can count on every day.

### ① Higher Productivity

This versatile, high-capacity trailer can get everything you need to the jobsite all year long:

- 49,850 lb capacity can handle mid-sized or multiple pieces of compact equipment in a single load.
- Secure any payload with 6 pairs of D-rings, 16 welded J-hooks, and 8 sliding 3-bar winches.
- Low 9° loading ramp angle made possible by combining a shallow 6' long dovetail, 6' long ramps, and a dual air bag tilting deck.

### ② Increased Durability

Top-quality finishes on the UBT2524 have the durability to keep your operation running smoothly:

- Premium protected wiring and LED lights ensure reliable electrical performance down to -58°F.
- The 6" C-channel cross members pierce the I-beam frame for increased rigidity and lower deck height.
- Three 25,000 lb axles provide support for large payloads.

### ③ Easy to Own

The UBT2524 is the easiest trailer to own:

- Customize your trailer with a rugged pneumatic ramp, providing easier and safer loading conditions for low clearance equipment.
- Easy to access and use controls for tilting the deck located in the tongue of the trailer and folding/unfolding ramps located at the rear of the deck
- Automatic deck lock system secures the deck in transport position for safe and effortless loading, unloading.

Powerful Value. **Delivered.**

# SPECIFICATIONS UBT2524 TILT DECK TRAILER

RAMP STYLE	Air Ramp		No Ramp	
	Spring Suspension	Air Suspension	Spring Suspension	Air Suspension
Reliability - Rated Capacity				
GVWR (lb)	63,100		63,100	
Rated Payload (lb)	49,860	47,550	49,850	49,050
Tongue Weight (lb)	9400		9400	
Suspension	Heavy Duty Spring Suspension	Air Ride Suspension	Heavy Duty Spring Suspension	Air Ride Suspension
Axle Rating (lb)	3 x 25,000		3 x 25,000	
Durability - Structure				
Frame Size	14" I-Beam		14" I-Beam	
Decking Material	2" Premium Fir		2" Premium Fir	
Surface Finish	Zinc-Based Primer with Dark Grey Powder-Coat Paint			
Beavertail Material	Planked Inside, Self-Cleaning Outside			
Crossmembers	6" Channel			
Side Rails	8" Channel			
Dimensions				
Total Length (ft)	37.8		37.5	
Fixed Deck Length (ft)	24		24	
Beaver Tailer Length (ft)	6		6	
Deck Width (in) – inside fender to fender	102		102	
Deck Height (in)	34.5		34.5	
Deck Tilt Approach Angle	9°		18°	
Included Equipment				
Hitch Type	Pintle		Pintle	
Jackleg Wind Type – top or side	Side		Side	
Jackleg Speeds	Dual		Dual	
Jackleg Lift Capacity (lb)	62,500		62,500	
Tire Size	ST235/75/R17.5 LRJ		ST235/75/R17.5 LRJ	
Premium Radial 20 ply Tires – speed rated to 120 kph	●		●	
Brakes	Air Drum Brakes w/ 2S/2M ABS		Air Drum Brakes w/ 2S/2M ABS	
Easy to Operate - Safety & Convenience Features				
Tie Downs	8x 3-Bar Sliding Winches, 16x J-Hooks, 6 pairs of D-rings			
Air Folding Flip-Up Ramps – 79 x 39"	●			
Dual Chains c/w Hook Latches – 36"	●		●	
Premium Protected Wiring	●		●	
Tier 1 LED Lighting System	●		●	
Oil Bath Axle Bearings	●		●	
Additional Features				
Lockable Toolbox in Tongue	●		●	
Mud Flaps	●		●	

## Auto-Locking Deck

Self-locking mechanism secures the deck for transport as soon as it is returned to the horizontal position.

## Extra Storage Space

Locking toolbox in the tongue of the trailer provides a convenient location for tools, chains, and more.

## Premium Fir Decking

High-quality hardwood decking lasts longer than pressure-treated options and provides a safe working space.

AVAILABLE ACCESSORIES: Locks for hitches ● Included at no extra cost

Specifications and descriptions applicable to change. Display option is not standard.

Revised 12/2023-U