

LEAD  
THE  
FIELD.



# Oilseed-Certified™ Harvest GrainBelts

## 2 YEAR EXTENDED WARRANTY

To ensure that your equipment is always ready to work when you need it, Brandt backs its products with a two-year limited warranty. *Ask us for details.*



## Far-Reaching Versatility.

Brandt's all-new Oilseed-Certified™ Harvest GrainBelts deliver gentle, efficient grain handling for any crop, including canola. Their unmatched versatility allows you to move all of your commodities with superior reach and high output. And, they're covered by our one-year standard warranty, plus one-year extended warranty, so you can work worry-free.

### ① Purpose-built

Move your oilseed with confidence using Brandt's specially designed belt:

- Industry-unique rubber belt will not degrade from handling oilseed.
- V-shape belt pattern with raised edges centres product on the belt.
- Manufacturer warranty is not limited by use in oilseed production, an industry first.

### ② Product Retention

New design protects your equipment and your crop by preventing leakage:

- Gentle conveying saves your crop from the damage associated with conventional augers.
- Fortified sealing throughout the transition and intake keep your product on the belt.
- Specialized sealing at critical points dramatically reduces leakage compared to standard conveyors.

### ③ Effortless Cleanout

Minimize manual cleanout with the Oilseed-Certified™ GrainBelts' self-cleaning system:

- Self-cleaning system clears the belt at critical points, virtually eliminating crushed oilseed build-up.
- Roller guarding and cleanout ports clear the backside of the belt.
- Flexible wipers maintain consistent contact with the belt, gently removing any build-up without damaging the belt.

Powerful Value. **Delivered.**

**Brandt**

# OILSEED-CERTIFIED™ HARVEST GRAINBELTS

## SPECIFICATIONS

	<b>15 Series</b> 1580A, 1590A, 15100A	<b>20 Series</b> 2095A, 20110A, 20125A	<b>24 Series</b> 2495A, 24110A, 24125A
<b>Performance</b>			
Capacity	Up to 6,200 bu/hr	Up to 12,000 bu/hr	Up to 14,000 bu/hr
<b>Dimensions</b>			
Belt Width	15"	20"	24"
Tube Size	10"	14"	14"
Conveyor Length	80' - 100'	95' - 125'	95' - 125'
Raised Height	33'1" - 41'6"	50' - 65'0.5"	50' - 65'0.5"
Raised Reach	31'7" - 42'9"	45'3" - 57'9"	45'3" - 57'9"
Lowered Reach	36'10" - 51'	51'1" - 65'7.5"	51'1" - 65'7.5"
Transport Height	12'11" - 13'6"	13'7" - 16'0.5"	13'7" - 16'0.5"
Transport Length	80' - 100'	98'3.5" - 128'6"	98'3.5" - 128'6"
Wheel Track Width	12'2"	13' - 13'4"	13' - 13'4"
Total Weight (lb)	6,228 - 6,710	11,686 - 13,437	13,553 - 15,317
Tire Size	225/75R15 8PLY	ST235/85R16 (95'); IF320/70R15 (110', 125')	ST235/85R16 (95'); IF320/70R15 (110', 125')
Hydraulic Cylinder Size (Bore x Stroke)	4.5" x 30" (80', 90'); 5" x 30" (100')	4.5" x 30" (95'); 5" x 36" (110', 125')	4.5" x 30" (95'); 5" x 36" (110', 125')
<b>Features</b>			
Windguards	Standard Welded	Standard Welded	Standard Welded
Belt Type	Oilseed-Certified™	Oilseed-Certified™	Oilseed-Certified™
Drive System	S-Drive	S-Drive	S-Drive
Swing Drive System	Hydraulic	Electric or Hydraulic	Electric or Hydraulic
<b>Low Profile Hopper</b>			
Hopper Dimensions (L x H)	36" x 70"	72" x 40"	72" x 40"
Hopper Height (lowered)	7.5"	10"	10"
Hopper Height (raised)	16"	18"	18"

## FEATURES

### Redesigned Scissor-lift Undercarriage

Delivers greater strength and rigidity when the conveyor is raised for smooth operation and maximum reach.

### EZTRAK Tensioning and Tracking System

Keeps the belt aligned a properly tensioned at all times, and provides an easy-to-see visual indication of when adjustments are needed.

### Solid Wind Guards and Reinforced Tube

Incorporates welded side panels for added tube strength and protection from the elements.

### High-traction S-drive

Allows superior belt contact on the large drive roller for increased drive traction, while belt take-up has been increased to 35" for improved tensioning.

### Integrated Swing-Away Intake

Positioned for maximum clearance, reach, and capacity.

### Options to Fit Your Needs

Including LED work and safety light kits, hydraulic steering kit, pivot axle kit for bunker piling, and capacity-matching transfer belts.

For more information  
Call us at 1-866-4-BRANDT  
Email us at [agriculture@brandt.ca](mailto:agriculture@brandt.ca)  
Or visit us at [www.brandt.ca](http://www.brandt.ca)

**Brandt Agricultural Products**  
PO Box 317, 13th Avenue & Pinkie Road,  
Regina, SK, Canada  
S4P 3A1

