

UBT822 TANDEM TILT			
	PERFORMANCE	PREMIUM	PREMIUM GALVANIZED
RELIABILITY - RATED CAPACITY			
GVWR (lb)	16,000	16,500	
Rated Payload (lb)	12,400	12,700	12,600
Tongue Weight (lb)	2000		
Suspension	Torsion - Bolt On		
Axle Rating (lb)	2 x 7000	2 x 8000	
Maximum Weight on Fixed Deck (lb)	2000		
DURABILITY - STRUCTURE			
HSS Mainframe Size (in)	8		
Decking Material	Premium Fir		
Surface Finish	Polyurethane Primer & Paint w/Rockguard	Polyurethane Primer & Paint w/Rockguard	Galvanized
DIMENSIONS			
Total Length (ft)	27.7		
Fixed Deck Length (ft)	6		
Tilt Deck Length (ft)	16		
Deck Width (in) – inside fender to fender	81.5	82.5	
Deck Height (in)	25		
INCLUDED EQUIPMENT			
Pull Type	Bumper		
Jackleg Wind Type - top or side	Side		
Jackleg Speeds	Single		
Jackleg Lift Capacity (lb)	10,000		
Hydraulic Cushion Cylinder	●		
Steel Tread Plate Fenders – bolt on	●		
Black Steel Wheels	●		
Wheel Size	16" Rim - 8 Stud - 6.5" Circle	17.5" Rim - 8 Stud - 6.5" Circle	
Tire Size	ST235/80R16 LRE	ST215/75R17.5LRH	
Premium Radial 10 ply Tires – speed rated to 120 kph	●		
Premium Radial 16 ply Tires – speed rated to 120 kph		●	
Aluminum Spoke Wheels	○		
EASY TO OPERATE - SAFETY & CONVENIENCE FEATURES			
Dual Chains c/w hook latches - 36"	●		
4 x 4" D-Rings	●		
Premium Protected Wiring	●		
Breakaway Switch – includes LED test lights, battery & charger	●		
Integral Footholds	●		
Lode N Lok Deck	●		
Tier 1 LED Lighting System	●		
Forward Self-Adjusting Brakes	●		
E-Z Lube Oil Bath Axle Bearings		●	
E-Z Lube Grease Axle Bearings	●		
Deck Traction Aid – expanded steel mesh	●		
Heavy Duty Toolbox	●		
ADDITIONAL FEATURES			
Mud Flaps	○		
Pallet Fork Holders	○	●	
Spare Tire, Wheel, & Carrier	○	●	
ACCESSORIES			
Tie Down Kit – 4 x 5000 lb WLL chains c/w hooks, 4 ratchets	○		
Coupler Lock	○		
Wheel Locks	○		
JD Link – fleet tracking	○		