

UBE518 UBE720

LOW-PROFILE FLATBED TRAILERS



2 YEAR WARRANTY

Unmatched 2-Year Bumper-to-Bumper Warranty on all components. 5-Year Structural Warranty. Ask us for details.

Trailer details may differ from image

Flat Out Results.

The Work Ready™ Brandt UBE518 and UBE720 low-profile flatbed trailers deliver superior capacity to get your agricultural or landscape equipment where it's going, every single day. These rugged models work as hard as you do, while taking all the punishment you can dish out.

1 Built to Last

Brandt trailers are purpose-built to maximize your productivity from dusk till dawn until the job gets done:

- A unified-frame design integrates the frame and deck into a single robust structure to minimize weak points and stress concentrations.
- Designed for optimal balancing with construction equipment, allowing for the most stable and secure load platform in the industry.
- Reliable design and long-lasting components reduce total cost of ownership.

2 Easier to Operate

These trailers are designed for fast, effortless loading so you can start working sooner:

- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.
- Expanded metal mesh accommodates equipment with ease, ensuring superior versatility.
- Standard tool tray located in the tongue of the trailer provides convenient storage and access to tools.

Safer

Safety is critical, so these models are designed with key features to maximize operator protection:

- Dependable 5200 lb axles (UBE518) and 7000 lb axles (UBE720) are standard to ensure positive hitch weight distribution and overall stability when hauling concentrated heavy payloads.
- Standard lower sidestep and bi-fold, fullwidth spring-assisted ramps with a knee support allow operators to work safely.
- Pressure treated pine/spruce decking provides better traction for the operator in wet and frozen conditions and reduces wear over time.



LOW-PROFILE FLATBED TRAILER TECHNICAL SPECIFICATIONS

QUICK REFERENCE CHART	UBE518 Low-Profile Flatbed	UBE720 Low-Profile Flatbed
RELIABILITY - RATED CAPACITY		
GVWR (lb)	9900	14,900
Rated Payload (lb)	7050	11,600
Tongue Weight (lb)	1250	1860
Suspension	Torsion - Bolt On	Torsion - Bolt On
Axle Rating (lb)	2 x 5200	2 x 7000
DURABILITY - STRUCTURE		
HSS Mainframe Size (in)	6	8
Pressure Treated Spruce/Pine Decking	•	•
Polyurethane Primer & Paint	Powder Top Coat, Polyester	Powder Top Coat, Polyester
DIMENSIONS		
Total Length (ft)	24.7	26.9
Fixed Deck Length (ft)	16	18
Dovetail Length (ft)	2	2
Deck Width (in) – inside fender to fender	82	82
Deck Height (in)	21	22
INCLUDED EQUIPMENT		
Pull Type	Bumper	Bumper
Jackleg Wind Type – top or side	Тор	Side
Jackleg Speeds	Single	Single
Jackleg Lift Capacity (lb)	7000	10,000
Steel Tread Plate Fenders – bolt on	•	•
Black Steel Wheels	•	•
Tire Size	ST225/75R15 LRE	ST235/80R16 LRE
Premium Radial 10 ply Tires – speed rated to 120 kph	•	•
EASY TO OPERATE - SAFETY & CONVENIENCE FEATURES		
Spring Assist Full Width Expanded Metal Mesh, Flip-Up w/ Knee Support Ramps – 82 x 60"	•	•
Steel Tread Plate Fenders – bolt on	•	•
Premium Protected Wiring	•	•
Breakaway Switch – includes LED test lights, battery & charger	•	•
Integral Footholds	•	•
Tier 1 LED Lighting System	•	•
Forward Self-Adjusting Brakes	•	•
E-Z Lube Grease Axle Bearings	•	•
Open Tool Tray	•	•
ACCESSORIES		
Coupler Lock	0	0
Wheel Locks	0	0