STRAIGHT BODY AND MAX BODY™

UBD814 | UBD916 | UGD916 | UBD1116 | UGD1116

DUMP TRAILERS



INDUSTRY BEST WARRANTY

2 YEAR WARRANTY

Unmatched 2-Year Bumper-to-Bumper Warranty on all components. 5-Year Structural Warranty. Ask us for details.

Trailer details may differ from image

Dump Downtime.

1 Built to Last

Brandt's trailers are purpose-built to maximize your productivity from dusk till dawn until the job gets done:

- Reliable design and long-lasting components reduce the total cost of ownership.
- Sturdy wide flange I-Beam main chassis plus an integral box subframe made of 5"channel and crossmembers every 16" prevent warping the floor over time.
- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.

Brandt Work Ready™ dump trailers are purpose-built to stand up against the toughest conditions, every day. Whether you're hauling equipment to the job site or aggregate when you're there, these trailers work as hard as you do and take all the punishment you can dish out.

Easier to Operate

These trailers are designed for fast, effortless loading so you can start working sooner:

- 2-way gate with slide out ramps or combo gate with integrated bi-folding ramps are giving you the perfect setup option for the task at hand.
- The power up, gravity down 3-stages telescopic cylinder improves lifting capacity throughout the course of the lift for easier dumping.
- A high-flow hydraulic power unit powered by a 12v deep cycle battery and backed up by a 110v shore charging plug-in for the intensive and repetitive work days.

Safer

Safety is critical on the job site, so these models are designed with key features to maximize operator protection:

- Stake pockets, D-rings and a heavy-duty tarp kit provide a no hassle, intuitive load securement.
- Easily accessible lifting mechanism and maintenance points, convenient ramps slide-in pockets, reliable lights powered by well-protected wiring, rare are the instances necessitating using the safety prop rod to go under the trailer for maintenance.
- Forward self-adjusting brakes keep the brakes at their peak performance for longer while eliminating the need for manual adjustments.



DUMP TRAILERS TECHNICAL SPECIFICATIONS

| QUICK REFERENCE CHART | UBD814 Tandem Bumper Pull | UBD/UGD916 Tandem Bumper Pull / Gooseneck | UBD/UGD1116 Tridem Bumper Pull / Gooseneck |
|---|-----------------------------------|--|---|
| Base Unit Key Specifications | Straight Body Max-Body™ | Straight Body Max-Body™ | Straight Body Max-Body™ |
| RELIABILITY - RATED CAPACITY | | | |
| GVWR (Ib) | 16,000 | 17,900 / 19,400 | 22,000 |
| Rated Payload (lb) – (painted finish) | 11,800 11,500 | 13,100 / 13,600 | 17,000 15,800 / 17,00 |
| Tongue Weight (lb) | 2000 | 2300/3800 | 3300 / 4400 |
| Suspension | | Slipper leaf spring with rubber bushin | g |
| Axle Rating (lb) | 2 x 7000 | 2 x 8000 | 3 x 7000 |
| Torsion Axles | 0 | 0 | 0 |
| DURABILITY – STRUCTURE & FINISH | | | |
| Wide Flange I-Beam Main Frame | 8" x 10 lb.ft | 8" x 10 lb.ft / 8" x 15 lb.ft | 8" x 10 lb.ft / 8" x 15 lb.ft |
| Subframe 5" Channel w/Crossmembers every 16" | • | • | • |
| Gate Type | | 2-Way | |
| Polyurethane Primer & Paint Finish | • | • | • |
| Slide Out Ramps 15 3/8" x 77" (made of 3" channels) | • | • | • |
| Heavy Duty 15 %" x 77" Slide Out Ramps (3" channel) | 0 | 0 | 0 |
| Heavy-Duty Combo Gate | 0 | 0 | 0 |
| Galvanized Finish | 0 | 0 | 0 |
| DURABILITY - DUMP BOX | | | |
| Bed Length (ft) | 14 | 16 | 16 |
| Bed Width (in)—floor/rim | 80/82 82/97 | 80/82 82/97 | 80/82 82/97 |
| Bed Material | | 10 Gauge Steel | |
| Side Walls Height (in) | 181/2 22 | 181/2 22 | 18 ½ 22 |
| Side Board Brackets | 0 | 0 | 0 |
| 3- Stage Telescopic Cylinder, Power Up/Gravity Down | • | • | • |
| High Flow Hydraulic Power Unit w/12v Deep Cycle Battery | • | • | • |
| 110V Shore Charging Plug In w/Charger | • | • | • |
| INCLUDED EQUIPMENT | | | |
| Steel Fenders—Bolt On | • | • | • |
| Tires | Premium Radial 10 ply, | Premium 16 ply, | Premium Radial 10 ply, |
| | ST235/80R16 LRE | ST215/75R17.5 LRH | ST235/80R16 LRE |
| 14- Ply Tires | 0 | | 0 |
| Jackleg 2-speed –12,000 lb capacity | Single | Single / Dual | Single / Dual |
| EASY TO OPERATE – SAFETY & CONVENIENCE FEAT | | | |
| Premium Protected Wiring | • | • | • |
| 4 x 4" D-Rings | | | • |
| Premium Heavy-Duty Tarp | | | |
| Tier 1 LED Lighting System | | | |
| Forward Self-Adjusting Brakes | | | |
| Stake Pockets | | | |
| Lockable Heavy-Duty Toolbox ADDITIONAL FEATURES | | | |
| | | | |
| Bucket Shelf—Max Body™ models | 0 | 0 | 0 |
| Rear Stabilizer Jacks | 0 | 0 | |
| Mud Flaps | 0 | 0 | 0 |
| Spare Tire Mount | 0 | 0 | 0 |
| Spare Tire | 0 | 0 | 0 |
| Box Lifting Warning Device | 0 | 0 | 0 |