

DUMP TRAILERS



INDUSTRY BEST WARRANTY

2 YEAR WARRANTY

Unmatched 2-Year Bumper-to-Bumper Warranty on all components. 5-Year Structural Warranty.

Ask us for details.

Trailer details may differ from image

Dump Downtime.

1 Built to Last

Brandt trailers are purpose-built to maximize your productivity from dusk till dawn, until the job gets done:

- Reliable design and long-lasting components reduce total cost of ownership.
- Reinforced floor with tire tracks to prevent warping over time.
- Unique design that lowers the deck height to generate lower loading angle.

2 Easier to Operate

the punishment you can dish out.

These trailers are designed for fast, effortless loading so you can start working sooner:

- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.
- The ideal gate and ramp configuration gives you the perfect setup for the task at hand.
- Power up, power down, gravity down hydraulic hoist cylinder delivers the muscle required to dump heavy loads with ease.

3 Safer

Brandt Work Ready™ dump trailers are purpose-built to stand up against the

equipment or aggregate, these trailers work as hard as you do and take all

toughest conditions, every day. Whether you're hauling agricultural or landscape

Safety is critical, so these models are designed with key features to maximize operator protection:

- Rugged slipper spring suspension system is optimized to safely distribute weight between axles when carrying heavy loads on uneven ground.
- Safety prop-rod secures the box in the raised position, maximizing operator safety while performing maintenance on the trailer.
- Forward self-adjusting brakes keep the brakes at their peak performance for longer while eliminating the need for manual adjustments.



DUMP TRAILERS TECHNICAL SPECIFICATIONS

QUICK REFERENCE CHART	UBD814 Tandem Straight Body	UPD1116 Tridem Straight Body	UGD1116 Tridem Straight Body
RELIABILITY - RATED CAPACITY			
GVWR (lb) – bumper pull/gooseneck	16,000	22,000	22,000
Rated Payload (lb) – bumper pull/gooseneck for painted finish	10,800	15,900/ 15,400	15,550/ 15,150
Tongue Weight (lb) – bumper pull/gooseneck	2000	2200/4400	2200/4400
Suspension	Torsion - Bolt On	Equalized Leaf Spring	Equalized Leaf Spring
Axle Rating (lb)	2 x 7000	3 x 7000	3 x 7000
DURABILITY - STRUCTURE & FINISH			
HSS Mainframe Size (in)	8" x 3"	8" x 3"	8" x 3"
Bed Material	10 Gauge Steel	10 Gauge Steel	10 Gauge Steel
Side Height and Material – if applicable	18" - 10 Gauge Steel	18" - 10 Gauge Steel	18" - 10 Gauge Steel
Polyurethane Primer & Paint Finish	•	•	•
DIMENSIONS			
Total Length (ft) – bumper pull/gooseneck	20.3	22/25.4	22.6/26
Bed Length (ft)	14	16	16
Bed Width (in) – floor/rim	82/82	82/82	82/82
Bed/Floor Height (in) – unloaded/loaded	25.3/23	25.3/23	25.3/23
INCLUDED EQUIPMENT			
Pull Type(s)	Bumper	Bumper	Gooseneck
Jackleg Speed	Single	Single	Single
Jackleg Lift Capacity (lb)	2 x 10,000	2 x 10,000	2 x 10,000
Steel Tread Plate Fenders – bolt on	•	•	•
Gate Type	2-Way	2-Way	Combo
Slide Out Ramps 6'6" x 10.5"	•	•	•
Power Up/Down, Gravity Down Hoist Cylinder	•	•	•
Black Steel Wheels	•	•	•
Aluminum Spoke Wheels	0	0	0
Tire Size	ST235/80R16 LRE	ST235/80R16 LRE	ST235/80R16 LRE
EASY TO OPERATE - SAFETY & CONVENIENCE	FEATURES		
Premium Protected Wiring	•	•	•
4 x 4" D-Rings	•	•	•
Breakaway Switch – includes LED test lights, battery & charger	•	•	•
Tier 1 LED Lighting System	•	•	•
Forward Self-Adjusting Brakes	•	•	•
E-Z Lube Grease Axle Bearings	•	•	•
110V Shore Charging Plug In	•	•	•
Heavy Duty Toolbox	•	•	•
Safety Prop Rod	•	•	•
HD Charge Kit	0	0	0
ADDITIONAL FEATURES			
Premium Heavy-Duty Tarp	•	•	•
' '			
Side Board Brackets			
Side Board Brackets Mud Flaps	0	0	0