

HX120 Spif Hydrovac

High-Pressure Performer.

The HX120 Spif hydrovac from Brandt delivers the unmatched productivity and precision you depend on in urban settings and beyond. It takes the guesswork out of weight restrictions and delivers maximized road-legal loads, lower noise levels, and exceptional maneuverability in tight spaces.

More Productive

Achieve quicker loading and unloading times of measured debris and take on larger jobs without weight restrictions:

- Accurate real-time measurement of water and truck weight and lower tare weight allows operators to confidently push payload to the maximum to get the most out of every trip without risking costly fines.
- Engineered from the ground up with optimally sized components and plumbing that work in harmony to maximize digging performance and increase legal payloads.
- The debris tank unloads more quickly and completely than competitors and has the ability to pressure offload into another truck, bin, or land spread for fast turnaround.

2 More Uptime

The HX120 Spif delivers unrivaled dependability, component reliability, and working hours:

- The full AR steel-constructed boom turret features an easily removable access plate for cleanout and shut-off plate that allows you to shut down the boom suction without having to shut down the blower.
- Industry-leading 28-foot boom features a progressive diameter from the dig tube to the turret, reducing plugging and acting as a secondary vacuum chamber that increases efficiency at the end of the hose.
- Easy access to service and maintenance points allow for quicker on-site servicing.
 And, remote sight glasses, grease lines, and oil drains save operators more time.

3 Lower Cost of Operation

The HX120 Spif is purpose-built with features that reduce the need for repairs and improves the lifespan of components:

- The 4000 CFM blower is powered by an innovative dual power takeoff, pulling full performance capability and eliminating the need for a transfer case.
- Fully powder coated debris tank resists corrosion, sheds mud more efficiently and features a wear plate directly under the boom turret, extending the life of the debris tank.
- Pulls similar vacuum compared to competitors at much lower RPM – keeping the worksite quieter while burning less fuel.



HX120 SPIF HYDROVAC SPECIFICATIONS

BASE UNIT KEY SPECIFICATIONS

Tare Weight Starting at 44,000 lb Debris Tank Capacity Water Capacity 11,5 VD Water Capacity 12,5 VD Water Capacity 13,5 VD Water Capacity 13,5 VD Water Capacity 14,5 VD Water Capacity 15,5 VD Water Capacity 16,5 VD Water Capacit		
Debris Tank Capacity Water Capacity 1150 USG Overall Height 11'11' Overall Height 11'11' Boom Reach 28, 340' Rotation CFLASSIS Chassis Make Peterbilt, Kenworth, or Custom Order Wheelbase Bojine & Horsepower Paccar MX, 450-510 Tansmission Allison 4500 Tank Layout Tank Layout Tank Layout Rear Door Safety Hydraulic Engaging Pin Out Design Rear Door Latch Hydraulic Latching System Flag Accuracy 4 Point Load Cell System VAC SYSTEM Blower Progressive Diameter, 8' Flex Hose, 10' Boom Piping, 12' Boom Turnet, Boom Isolation Valve Filtration Progressive Diameter, 8' Flex Hose, 10' Boom Piping, 12' Boom Turnet, Boom Isolation Valve Filtration Progressive Diameter, 8' Flex Hose, 10' Boom Piping, 12' Boom Turnet, Boom Isolation Valve Filtration Progressive Diameter, 8' Flex Hose, 10' Boom Piping, 12' Boom Turnet, Boom Isolation Valve Filtration Progressive Diameter, 8' Flex Hose, 10' Boom Piping, 12' Boom Turnet, Boom Isolation Valve Filtration Progressive Diameter, 8' Flex Hose, 10' Boom Piping, 12' Boom Turnet, Boom Isolation Valve Filtration Progressive Diameter, 8' Flex Hose, 10' Boom Piping, 12' Boom Turnet, Boom Isolation Valve Filtration Progressive Diameter, 8' Flex Hose, 10' Boom Piping, 12' Boom Turnet, Boom Isolation Valve Filtration Progressive Diameter, 8' Flex Hose, 10' Boom Piping, 12' Boom Turnet, Boom Isolation Valve Filtration Progressive Diameter, 8' Flex Hose, 10' Boom Piping, 12' Boom Turnet, Boom Isolation Valve Filtration Progressive Diameter, 8' Flex Hose, 10' Boom Piping, 12' Boom Turnet, Boom Isolation Valve Filtration Progressive Diameter, 8' Flex Hose, 10' Boom Piping, 12' Boom Turnet, Boom Isolation Valve Filtration Real 100' 3/8' Hose, Electric Retract CONTROL SYSTEM Hydraulics Push Button Controls Maine Grade, Cold Temp Rated Remote Remote Remote Pesigned for Single Page Control with Live Readout of Water Level, Turk Weight, and Pump Pressure. Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	CAPACITIES, DIMENSIONS, & RATINGS	
Water Capacity Overall Height Overall Height 11'11' Overall Height Bo' Overall Height Bo' Overall Height Boom Reach 28' 340' Rotation CHASSIS Chasis Make Peterbilt, Kenworth, or Custom Order Wheelbase 320' Fanjine & Horsepower Paccar MX, 450-510 Tansmission Allison 4500 TANK DESIGN Offloading Hoist, Pressure Offload, Full Open Rear Door, Hydraulic Vibrator Tank Layout Saddle Tank Design for Balanced Axie Weights Rear Door Safety Hydraulic Latching System High Accuracy 4 Point Load Cell System VAC SYSTEM. Blower High Accuracy 4 Point Load Cell System VAC SYSTEM. Blower Hibon 840 4000 CFM Vae Piping Progressive Diameter, 8' Flex Hose, 10' Boom Piping, 12' Boom Turret, Boom Isolation Valve Filtration Brandt Dual Cyclone & Cartridge Filter Jights SYSTEM WASH SYSTEM Wash Pump CAT 2560 16 GPM 8 3000 PSI Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel 100' 3/8' Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexorth Hydraulics Remote Remote Designed for Single Page Control with Live Readout of Witer Level, Turk Weight, and Pump Pressure. Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit.	Tare Weight	Starting at 44,000 lb
Overall Height Overall Width 86° Overall Width 86° Overall Length 381° Boom Reach 28;340° Rotation CHASSIS Chassis Make Peterbilt, Kenworth, or Custom Order Wheelbase 320° Engine & Horsepower Paccar MX, 450-510 Transmission Allison 4500 TANK DESIGN Offloading Hoist, Pressure Offload, Full Open Rear Door, Hydraulic Vibrator Tank Layout Saddle Tank Design for Balanced Axle Weights Rear Door Safety Hydraulic Latching System Scale System High Accuracy 4 Point Load Cell System VAC SYSTEM Blower Progressive Diameter, 8° Flex Hose, 10° Boom Piping, 12° Boom Turret, Boom Isolation Valve Filtration Brandt Dual Cychone & Cartridge Filter Dig Tubes 4 - 6° Poly Dig Tube Extensions WASH SYSTEM Wash Pystem Purpose Built 705k BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glyco Blowdown & Recovery System Real CONTROL SYSTEM Hydraulics Book Reworth Hydraulics Book Reworth Hydraulics Book Reworth Hydraulics Book Reworth Pydraulics Book Reworth Pydraulics Remote Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Miltipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Debris Tank Capacity	11.6YD
Overall Length Overall Length	Water Capacity	1150 USG
Overall Length Boom Reach 28, 340° Rotation CHASSIS Chassis Make Peterbilt, Kenworth, or Custom Order Wheelbase 320° Engine & Horsepower Paccar MX, 450-510 Transmission Allison 4500 TANK DESIGN Offloading Hoist, Pressure Offload, Full Open Rear Door, Hydraulic Vibrator Tank Layout Saddle Tank Design for Balanced Axile Weights Rear Door Safety Hydraulic Engaging Pin Out Design Rear Door Latch Hydraulic Latching System High Accuracy 4 Point Load Cell System VAC SYSTEM Blower Vac Piping Progressive Diameter, 8° Flex Hose, 10° Boom Piping, 12° Boom Turret, Boom Isolation Valve Filitration Brandt Dual Cyclone & Cartridge Filter Dig Tubes 4 + 6° Poly Dig Tube Extensions WASH SYSTEM Wash Pump CAT 2560 16 GPM & 3000 PSI Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel CONTROL SYSTEM Hydraulics Bosch Revroth Hydraulics Remote Remote Designed for Single Page Countrol with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Overall Height	11'11"
Boom Reach CHASSIS Chassis Make Peterbilt, Kenworth, or Custom Order Wheelbase 3320" Engine & Horsepower Paccar MX, 450-510 Transmission Allison 4500 TANIK DESIGN Offloading Hoist, Pressure Offload, Full Open Rear Door, Hydraulic Vibrator Tank Layout Saddle Tank Design for Balanced Axle Weights Rear Door Safety Hydraulic Latching System Hydraulic Latching System Scale System High Accuracy 4 Point Load Cell System VAC SYSTEM Blower Hibon 840 4000 CFM Vac Piping Progressive Diameter, 8" Flex Hose, 10" Boom Piping, 12" Boom Turret, Boom Isolation Valve Filtration Brandt Dual Cyclone & Cartridge Filter Dig Tubes 4-6" Poly Dig Tube Extensions WASH SYSTEM Wash Pump CAT 2560 16 GPM & 3000 PSI Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel 100" 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexroth Push Button Controls Remote Remote Designed for Single Page Control With Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Overall Width	8'6"
CHASSIS Chassis Make Peterbilt, Kenworth, or Custom Order Wheelbase 320" Engine & Horsepower Paccar MX, 450-510 Transmission Allison 4500 TANK DESIGN Offloading Hoist, Pressure Offload, Full Open Rear Door, Hydraulic Vibrator Tank Layout Saddle Tank Design for Balanced Axle Weights Rear Door Safety Hydraulic Engaging Pin Out Design Rear Door Latch Hydraulic Latching System Scale System High Accuracy 4 Point Load Cell System VAC SYSTEM Blower Hibon 840 4000 CFM Vac Piping Progressive Diameter, 8" Flex Hose, 10" Boom Piping, 12" Boom Turret, Boom Isolation Valve Filtration Brandt Dual Cyclone & Cartridge Filter Dig Tubes 4-6" Poly Dig Tube Extensions WASH SYSTEM Wash Pump CAT 2560 16 GPM & 3000 PSI Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel 100" 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexxoth Push Button Controls Ability to Control Required Functions from any Control Location on the Unit	Overall Length	38'1"
Chassis Make Peterbilt, Kenworth, or Custom Order Wheelbase 320" Engine & Horsepower Paccar MX, 450-510 Transmission Allison 4500 TANK DESIGN Offloading Hoist, Pressure Offload, Full Open Rear Door, Hydraulic Vibrator Tank Layout Saddle Tank Design for Balanced Axle Weights Rear Door Safety Hydraulic Engaging Pin Out Design Rear Door Latch Hydraulic Latching System Scale System High Accuracy 4 Point Load Cell System VAC SYSTEM Blower Hibon 840 4000 CFM Vac Piping Progressive Diameter, 8" Flex Hose, 10" Boom Turret, Boom Isolation Valve Filtration Brandt Dual Cyclone & Cartridge Filter Dig Tubes 4-6" Poly Dig Tube Extensions WASH SYSTEM Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel 100" 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexord Push Button Controls Ability to Control Required Functions from any Control Location on the Unit	Boom Reach	28', 340° Rotation
### Brain ### Br	CHASSIS	
Engine & Horsepower Transmission Allison 4500 TANK DESIGN Offloading Hoist, Pressure Offload, Full Open Rear Door, Hydraulic Vibrator Tank Layout Saddle Tank Design for Balanced Axle Weights Rear Door Safety Hydraulic Engaging Pin Out Design Rear Door Latch Hydraulic Latching System Scale System High Accuracy 4 Point Load Cell System VAC SYSTEM Blower Hibon 840 4000 CFM Vac Piping Progressive Diameter, 8" Flex Hose, 10" Boom Piping, 12" Boom Turret, Boom Isolation Valve Filtration Brandt Dual Cyclone & Cartridge Filter Dig Tubes 4-6" Poly Dig Tube Extensions WASH SYSTEM Wash Pump CAT 2560 16 GPM & 3000 PSI Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel 100" 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Remote Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Chassis Make	Peterbilt, Kenworth, or Custom Order
Transmission Allison 4500 TANK DESIGN Offloading Hoist, Pressure Offload, Full Open Rear Door, Hydraulic Vibrator Tank Layout Saddle Tank Design for Balanced Axle Weights Rear Door Safety Hydraulic Engaging Pin Out Design Hydraulic Latching System High Accuracy 4 Point Load Cell System VAC SYSTEM Blower Hibon 840 4000 CFM Vac Piping Progressive Diameter, 8" Flex Hose, 10" Boom Piping, 12" Boom Turret, Boom Isolation Valve Filtration Brandt Dual Cyclone & Cartridge Filter Dig Tubes 4-6" Poly Dig Tube Extensions WASH SYSTEM Wash Pump CAT 2560 16 GPM & 3000 PSI Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel 100" 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexroth Hydraulics Remote Remote Pesigned for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Wheelbase	320"
TANK DESIGN Offloading Hoist, Pressure Offload, Full Open Rear Door, Hydraulic Vibrator Tank Layout Saddle Tank Design for Balanced Axle Weights Rear Door Safety Hydraulic Engaging Pin Out Design Hydraulic Latching System Scale System High Accuracy 4 Point Load Cell System VAC SYSTEM Blower Hibon 840 4000 CFM Vac Piping Progressive Diameter, 8" Flex Hose, 10" Boom Piping, 12" Boom Turret, Boom Isolation Valve Filtration Brandt Dual Cyclone & Cartridge Filter Dig Tubes 4 - 6" Poly Dig Tube Extensions WASH SYSTEM Wash Pump CAT 2560 16 GPM & 3000 PSI Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Real 100" 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexroth Hydraulics Remote Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Engine & Horsepower	Paccar MX, 450-510
Hoist, Pressure Offload, Full Open Rear Door, Hydraulic Vibrator	Transmission	Allison 4500
Tank Layout Rear Door Safety Hydraulic Engaging Pin Out Design Rear Door Latch Hydraulic Latching System Scale System High Accuracy 4 Point Load Cell System VAC SYSTEM Blower Hibon 840 4000 CFM Vac Piping Progressive Diameter, 8" Flex Hose, 10" Boom Piping, 12" Boom Iurret, Boom Isolation Valve Filtration Brandt Dual Cyclone & Cartridge Filter Dig Tubes 4 - 6" Poly Dig Tube Extensions WASH SYSTEM Wash Pump CAT 2560 16 GPM & 3000 PSI Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel CONTROL SYSTEM Hydraulics Bosch Rexroth Push Button Controls Remote Remote Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	TANK DESIGN	
Rear Door Safety Rear Door Latch Rear Door Latch Scale System Hydraulic Latching System High Accuracy 4 Point Load Cell System VAC SYSTEM Blower Hibon 840 4000 CFM Vac Piping Progressive Diameter, 8" Flex Hose, 10" Boom Piping, 12" Boom Turret, Boom Isolation Valve Filtration Brandt Dual Cyclone & Cartridge Filter Dig Tubes 4 - 6" Poly Dig Tube Extensions WASH SYSTEM Wash Pump CAT 2560 16 GPM & 3000 PSI Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Reel 100" 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexroth Push Button Controls Remote Remote Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Offloading	Hoist, Pressure Offload, Full Open Rear Door, Hydraulic Vibrator
Rear Door Latch Scale System High Accuracy 4 Point Load Cell System VAC SYSTEM Blower Hibon 840 4000 CFM Vac Piping Progressive Diameter, 8" Flex Hose, 10" Boom Piping, 12" Boom Turret, Boom Isolation Valve Filtration Brandt Dual Cyclone & Cartridge Filter Dig Tubes 4 - 6" Poly Dig Tube Extensions WASH SYSTEM Wash Pump CAT 2560 16 GPM & 3000 PSI Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel 100' 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexroth Push Button Controls Remote Remote Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Tank Layout	Saddle Tank Design for Balanced Axle Weights
Scale System	Rear Door Safety	Hydraulic Engaging Pin Out Design
Wash Pump Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Real Bosch Rexroth Hibon 840 4000 CFM Progressive Diameter, 8" Flex Hose, 10" Boom Piping, 12" Boom Turret, Boom Isolation Valve Brandt Dual Cyclone & Cartridge Filter Dig Tubes 4 - 6" Poly Dig Tube Extensions WASH SYSTEM Wash Pump CAT 2560 16 GPM & 3000 PSI Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel 100" 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexroth Push Button Controls Remote Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Rear Door Latch	Hydraulic Latching System
Blower Hibon 840 4000 CFM Vac Piping Progressive Diameter, 8" Flex Hose, 10" Boom Piping, 12" Boom Turret, Boom Isolation Valve Filtration Brandt Dual Cyclone & Cartridge Filter Dig Tubes 4-6" Poly Dig Tube Extensions WASH SYSTEM Wash Pump CAT 2560 16 GPM & 3000 PSI Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel 100' 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexroth Push Button Controls Marine Grade, Cold Temp Rated Remote Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Scale System	High Accuracy 4 Point Load Cell System
Vac Piping Progressive Diameter, 8" Flex Hose, 10" Boom Piping, 12" Boom Turret, Boom Isolation Valve Filtration Brandt Dual Cyclone & Cartridge Filter Dig Tubes 4 - 6" Poly Dig Tube Extensions WASH SYSTEM Wash Pump Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel 100" 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexroth Push Button Controls Marine Grade, Cold Temp Rated Remote Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	VAC SYSTEM	
Filtration Brandt Dual Cyclone & Cartridge Filter Dig Tubes 4 - 6" Poly Dig Tube Extensions WASH SYSTEM Wash Pump CAT 2560 16 GPM & 3000 PSI Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel 100' 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexroth Push Button Controls Remote Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Blower	Hibon 840 4000 CFM
Dig Tubes ### A - 6" Poly Dig Tube Extensions #### A - 6" Poly Dig Tube Extension #### A - 6" Poly Dig Tube Extension #### A - 6" Poly Dig Tube Ex	Vac Piping	Progressive Diameter, 8" Flex Hose, 10" Boom Piping, 12" Boom Turret, Boom Isolation Valve
WASH SYSTEM Wash Pump CAT 2560 16 GPM & 3000 PSI Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel 100' 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexroth Push Button Controls Marine Grade, Cold Temp Rated Remote Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Filtration	Brandt Dual Cyclone & Cartridge Filter
Wash Pump CAT 2560 16 GPM & 3000 PSI Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel 100' 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexroth Push Button Controls Marine Grade, Cold Temp Rated Remote Remote Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Dig Tubes	4 - 6" Poly Dig Tube Extensions
Boiler Purpose Built 705K BTU, Fuel Efficient Combustion Chamber Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel 100' 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexroth Push Button Controls Marine Grade, Cold Temp Rated Remote Remote Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	WASH SYSTEM	
Winterization Heated Valves & Water lines, Glycol Blowdown & Recovery System Reel 100' 3/8" Hose, Electric Retract CONTROL SYSTEM Hydraulics Bosch Rexroth Push Button Controls Marine Grade, Cold Temp Rated Remote Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Wash Pump	CAT 2560 16 GPM & 3000 PSI
Reel CONTROL SYSTEM Hydraulics Bosch Rexroth Push Button Controls Remote Remote Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Boiler	Purpose Built 705K BTU, Fuel Efficient Combustion Chamber
Hydraulics Bosch Rexroth Push Button Controls Marine Grade, Cold Temp Rated Remote Remote Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Winterization	Heated Valves & Water lines, Glycol Blowdown & Recovery System
HydraulicsBosch RexrothPush Button ControlsMarine Grade, Cold Temp RatedRemoteRemote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare RemoteMultipoint ControlsAbility to Control Required Functions from any Control Location on the Unit	Reel	100' 3/8" Hose, Electric Retract
Push Button Controls Marine Grade, Cold Temp Rated Remote Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	CONTROL SYSTEM	
Remote Designed for Single Page Control with Live Readout of Water Level, Truck Weight, and Pump Pressure. Unit includes a spare Remote Multipoint Controls Ability to Control Required Functions from any Control Location on the Unit	Hydraulics	Bosch Rexroth
Multipoint Controls Unit includes a spare Remote Ability to Control Required Functions from any Control Location on the Unit	Push Button Controls	Marine Grade, Cold Temp Rated
	Remote	
Lighting Full LED Worklighting around the Unit and on Boom End	Multipoint Controls	Ability to Control Required Functions from any Control Location on the Unit
	Lighting	Full LED Worklighting around the Unit and on Boom End

STORAGE & ENCLOSURE	
PS Wash Cabinet	Heated Operator Enclosure
PS Rear Controls Cabinet	Heated Storage in Option
DS Rear Cabinet	Vertical Dig Tube and Accessory Storage
DS Vac Cabinet	Heated Storage in Option
DS & PS Bumper Storage	Cold Storage
DURABILITY	
Paint Finish	Zinc Primer + Polyester Powdercoat
Tank Coating	Zinc Primer + Polyester Powdercoat
Tank Floor Liner	UHMW
Boom Liner	Full Length Rotatable Boom Liner
Boom Turret	Full AR Plate Construction
Debris Unloading Extension	Bolt-On UHMW
Remote Grease Lines	Ground Level Grease Points for easy Maintenance
Premium Grade Electrical	Braided Loom and Weather Proof Connections throughout the Unit. Marine Grade Controls
KEY OPTIONS	
Remote Hose Storage Tray	0
Landspread	0
Pressure Offload	0
High Voltage Proximity Detection	0
Full Surround Camera Package	0
Cyclone Quick Clean Out	0
Rear Signboard	0
Wash Wand Package	0
Diesel Coolant Heater System	0
High Visibility Fluid Level Indicators	0
Decant Valve Package	0
Second Wash Reel	0
Corded Work Light	0
Quick Attach Life Line	0
Static Reel	0
Trailering Package	0
Blower Diesel Flush	0



Quietest-Running Truck

The Brandt-engineered vacuum system components minimize space requirements, increasing component performance and optimizing noise suppression. Enclosed cyclones, filter, and sheltered blower design greatly reduce noise.

SPIF-23 Compliant

The HX120 Spif Hydrovac incorporates a self-steering lift axle that meets Ontario transportation regulations.

Payload Accuracy

4-point load cell system provides "class leading" real time measurement of debris, water and truck weight for extremely accurate legal load management.

Compact Design

The automatic transmission, low overall height, and compact wheelbase deliver superior maneuverability, making it easier to operate.

Simple and Reliable Marine-Grade Control Panels

The HX120 spif is equipped with multiple locations to operate work lights, activate hydraulics, and control the wash pump, saving the operator unnecessary trips around the unit. And, all functions are controllable directly from the work area.

Multiple Storage Cabinets

Quick access to tools on the driver, passenger, and rear sides (including the bumper) enables operators to work efficiently at the jobsite. And, a warming/change cabinet allows operators to warm up or change out of wet work gear.

Cold Weather Package

Winter-friendly components ensure yearround operation in colder climates. Plus, the anti-freeze system, complete with recovery, allows outdoor parking without damaging the water pump and lines.

Boom Isolation Valve

Conveniently shut off the vacuum at the end of the hose without shutting down the blower.

Rear Door Safety Lockout

The rear-door safety lockout ensures safe servicing and allows operators to wash down the inside of the debris tank with ease. Plus, the system requires less water to wash out after unloading than competitor slope-unload designed units.

Wireless Controls

All functions appear on the main page for enhanced efficiency at the jobsite and the quick start feature enables operators to start excavating and adjust performance with the push of a button.

Top-Of-Tank Access Ladder

Independent grab points ensure easy access to the top of the tank with a progressive entry walkway and full-length non-slip area integrated into the top of the debris tank.

Optimized Water System

The optimum sized water pump and boiler provide increased efficiency and productivity with unmatched performance. Plus, the quick-fill poly water tanks save time and weight.

