



TRAILER
H600

JEEP
R40

PIN-ON AXLE
PM10

BOOSTER
V10

60-TON HIGHWAY TRAILERS



INDUSTRY BEST WARRANTY

3 YEAR WARRANTY

1 Year Bumper-to-Bumper Warranty on all components. Extended warranty up to 3 years available at extra cost. *Ask us for details.*

FLEXIBLE FINANCING

Custom financing solutions available to best suit your business. *Ask us for details.*

Haul It All.

The H600 multi-axle heavy haul trailer gives you the flexibility to haul it all, from standard to specialized loads, with ease.

① Easier to Own

Our team is here to support you every step of the way and make owning the H600 hassle-free with:

- Flexible in-house purchasing options including rentals, leasing, and conventional financing are available to suit your financing needs.
- Brandt's advanced paint protection provides better longevity and corrosion protection to keep your trailer looking like new for longer.
- Reliable design with long-lasting components lowers the total cost of ownership.

② Easier to Operate

You deserve a trailer that works as hard as you do. That's why we optimized the H600 with:

- Simple, robust gooseneck connection that gets you on the road faster, even in rough terrain.
- Five-position ride height valve is included standard and can quickly adapt to suit any road conditions.
- Brandt's industry-leading 14HP EFI powerpack delivers maximum lift capacity at a higher flow rate to save you time and money.

③ Safer to Own

Safety is critical on the jobsite, and the H600 is designed with features that maximize operator protection, including:

- Extra-stroke shim legs that eliminate pinch points allow shims to be added or removed safely when adjusting the deck height.
- Rugged, built-in lift points on the end ramps ensure risk-free ramp removal.
- Remotely mounted air tank drain valves make completing daily maintenance faster and easier.

Powerful Value. **Delivered.**

Brandt



FEATURES

Low-profile Gooseneck

Delivers more space for maximum payload and optimized mounting for air and electrical connections. Simple, mechanical connection is more robust and easily connects to the trailer on uneven ground.

Abrasion-resistant Paint

Maximizes trailer life and resale value with the industry's most durable powder-coat finish.

14 HP EFI Engine

Delivers 57% faster flow-rate than the competition while maintaining maximum lift capacity. Save time and money with faster starts, reduced downtime, and better fuel economy.

Longer Standard Knuckle Trough

Allows your excavator to sit 5" lower and could save you an over-height permit.

Five-position Ride Height Valve

Easily adjusts to varying terrain.

Increased Fifth-wheel Slide

Delivers 7" of fifth-wheel adjustment enables the jeep to accommodate a wider variety of equipment.

Built-in Lift Points on End Ramps

Allows you to easily remove ramps with a forklift and sling.

Remote Air Tank Drain-valves

Saves you valuable time on maintenance.

Unlimited Neck Shimming

Utilizes spring-loaded shim legs with extra stroke, making it easy and safe to add or remove shims.

Rebound-limiting Chains

Protect the shocks so your equipment lasts longer.

Individual Suspension Shut-off

Extends tire life by lifting an axle when travelling empty.

Wide Stinger

Delivers improved stability when removing the gooseneck.

Optional Features

- Auto-Shim Spreader/Pin-On Axle Booster
- Pin-on 4th Axle
- Brandt V10 Slingshot Booster
- Removable Rear Fenders
- Lift Kit for 3rd and/or 4th Axle
- Steel Swing-out Outriggers
- Removable Deck End Ramps
- Drop Side Deck

SPECIFICATIONS H600 TRAILER

BASE UNIT KEY SPECIFICATIONS

RELIABILITY - RATED CAPACITY			
Rated Load on 16' (ton)	60		
Nominal Axle Wall Thickness (in)	3/4		
DURABILITY - STRUCTURE			
Decking/Floor Material	3" Fir		
Paint Finish	Zinc Primer + Polyester Powder Coat		
DIMENSIONS			
Deck Length (ft)	24	26	
Overall Length (ft)	52'11"-54'11" Tridem	56'3"-58'3" Quad	
Wheelbase (ft) - 88" KP	41'11"-43'11" Tridem	41'7"-42'7" Quad	
Deck Width (ft)	8'6"	9	10
Axle Spacing (in)	54	60	
Running Gear Width (ft)	8'6"	9	10
Loaded Deck Height (in)	22" at 6" Ground Clearance		
Loaded Ground Clearance (in)	Adjustable 5 Settings: 6.5" - 9.5"		
Upper Coupler Height (in)	50		
Gooseneck Swing (in)	88, 112, 154, 172 w/ GN Ext.		
GOOSENECK FEATURES			
Hydraulic Actuated, Spring Loaded Shim Block	●		
Gooseneck Extension for Tandem Jeep	○		
Aluminum Fenders, Removable Back 1/3	○		
Hydraulic Flip Kit	○		
Swingout Lights	○		
Work Lights	○		
Dual Source Hydraulics - 14HP EFI Engine, Wet Kit Diverter Valve	○		
Low Profile Neck	●		

Deck Features		
Low Profile Front Loading Ramps	●	
D-Rings on Front Loading Ramps, Inside & Outside	●	
Chain Pockets Every 4' on Outside of Web	●	
8 Internal Chain Pockets	●	
Knuckle Trough - Last 6' of Deck	●	
Full Deck Knuckle Trough	○	
2 Formed Wire Mesh Chain Baskets	●	
Pin Joint Connection to Rear Frame, Includes Built in Shims	●	
Clip in Outriggers Every 2'	○	
2 Pairs of Swingout Lights	○	
Bolt in Slip Resistant Knuckle Trough Cover	○	
Lockable Aluminum Storage Box Lid	○	
Removable Deck End Ramps	○	
Bolted Rubber Belting on Decking	○	
6' Deck Extension	○	
Deck Extension Outriggers	○	
Bolt in Slip Resistant Deck Extension Trough Cover	○	
Suspension Frame Features		
Suspension Style	Tridem	Quad
Drum Brakes	●	
PAN22 Disc Brakes	○	
8.25 X 22.5" Aluminum Wheels	○	
275/70R22.5 Michelin X MLT Z Highway Tires	○	
Rebound Limiters & Air Bag Shutoffs	●	
Removable HMW Fenders	○	
Battery Back-up Kit for Strobes	○	
Slip Resistant Boom Trough Cover	○	
Remote Drain Valve Accessible on Outside of Frame	●	
Load Bearing Bolsters with Chain Pockets	●	
Mudflaps	●	
5 Position Ride Height Valve	●	
Strobe Lights	●	
Easy to Own - Purchase Options		
Cash, Rent or Lease*, Low Rate Lease*	○	
Peace of Mind - Warranty		
1 Year - Comprehensive Bumper to Bumper	●	
2 Year - Comprehensive Bumper to Bumper	○	
3 Year - Comprehensive Bumper to Bumper	○	

● Included at no extra cost

○ Option available

*See Dealer for Details

R40 JEEP

Base Unit Key Specifications	
Reliability - Rated Capacity	
Rated Load (ton)	40
Nominal Axle Wall Thickness (in)	5/8
Durability - Structure	
Paint Finish	Zinc Primer + Polyester Powder Coat
Dimensions	
Overall Length (ft)	26'6"
Wheelbase (ft)	19'3"
Running Gear Width (ft)	8'6"
Loaded 5th Wheel Height (in)	53
Upper Coupler Height (in)	50
Axle Spacing (in)	49
5th Wheel Travel (in)	94
Tractor Swing Clearance (in)	79/100
Jeep Swing (in)	168
Gooseneck Features	
Aluminum Fenders, Including Mudflap	○
Spare Tire Carrier	○
Hydraulic Lines for Wet Kit Connection	○
Main Frame Features	
Premium 2 Speed Landing Gear	●
Brake Release Valve	●
Suspension Dump Valve	●
Suspension Air Gauge	●
Weatherproof Lid to House Air Valves	●
Remote Drain Valve Accessible on Outside of Frame	●
Mudflaps	●
Chain Pockets for Lifting	●
Suspension Frame Features	
Drum Brakes	●
PAN22 Disc Brakes	○
8.25 X 22.5" Aluminum Wheels	●
275/70R22.5 Bridgestone M840 On/Off Road Tires	○
Rebound Limiters & Air Bag Shutoffs	●
Rear Ramps Accommodate Mechanical Gooseneck Trailers	●
Easy to Own - Purchase Options	
Cash, Rent or Lease*, Low Rate Lease*	○
Peace of Mind - Warranty	
1 Year - Comprehensive Bumper to Bumper	●
2 Year - Comprehensive Bumper to Bumper	○
3 Year - Comprehensive Bumper to Bumper	○

PM10 PIN-ON AXLE

BASE UNIT KEY SPECIFICATIONS			
RELIABILITY - RATED CAPACITY			
Capacity (ton)	10		
Use With	C550, H600		
DIMENSIONS			
Overall Length (ft)	5'4"		
Running Gear Width (ft)	8'6"	9	10
Interaxle Spacing (in)	54		60
Connection Type	Pin On - 38" Lug Center, 20" Pin Couple, 1.5" Pin		
MAIN FRAME			
Main Frame Type	No Hassle Flip Lugs, Load Bearing Front Bolster & Lightbar		
Beams	Fabricated, 100 ksi Flanges & Webs		
Load Securement	2 Pair of D-Rings for Flipping or Tie-Down		
Suspension Capacity	(1) x HT250 25,000 lb		
Axle Capacity (Nominal)	22,500 lb per axle, 5/8 wall		
Hubs	Duralite, 75W90 Synthetic Gear Oil, 10-Stud		
Air System	FMVSS, CMVSS Compliant, Common Air Operation, Remote Air Tank Drain Valves		
Electrical System	FMVSS, CMVSS Compliant, LED Lighting, 4" Bumper Mounted Strobes with Switch in Control Box, OEM Weatherseal Harnessing		

AUTO-SHIM SPREADER

BASE UNIT KEY SPECIFICATIONS

RELIABILITY - RATED CAPACITY	
Capacity (ton)	10
Use With	C550, H600
DIMENSIONS	
Overall Length (ft)	10'4"
Interaxle Spacing (in)	14'7"
Connection Type	Pin On - 38" Lug Center, 20" Pin Couple, 1.5" Pin, Top Hook for Easy Connection
MAIN FRAME	
Main Frame Type	Center Spine, Vertical Frame Pivot for Steering
Beams	Fabricated, 100 ksi Flanges & Webs
Shim Method	Automatic Shim, Automatic Relief
Electrical System	Strobes with Switch in Control Box, OEM Weatherseal Harnessing


V10 BOOSTER

BASE UNIT KEY SPECIFICATIONS


RELIABILITY - RATED CAPACITY	
Capacity (ton)	10
Use With	C550, H600, H650, H750
DIMENSIONS	
Overall Length (ft)	13'
Running Gear Width (ft)	8'6"
Interaxle Spacing (in)	14'1"
Connection Type	Pin On - 38" Lug Center, 20" Pin Couple, 1.5" Pin, Top Hook for Easy Connection
MAIN FRAME	
Main Frame Type	Center Spine, Vertical Frame Pivot for Steering
Beams	Fabricated, 100 ksi Flanges & Webs
Load Securement	2 Pair of D-Rings for Flipping or Tie-Down
Suspension Capacity	25,000 lb
Axle Capacity (Nominal)	22,500 lb per axle, 5/8 wall
Hubs	Duralite, 75W90 Synthetic Gear Oil, 10-Stud
Shim Method	Manual Shimming
Air System	FMVSS, CMVSS Compliant, Weather Sealed Air Controls Including Suspension Air Gauge, Common Air for HT250 Suspension and Regulated Air Override Suspension Settings, Spring Brake Release Valve, Remote Air Tank Drain Valves
Electrical System	FMVSS, CMVSS Compliant, LED Lighting, 4" Bumper Mounted Strobes with Switch in Control Box, Control Box Lighting, OEM Weatherseal Harnessing, Rear 7-way Socket for Auxiliary Lighting

60-TON HIGHWAY TRAILER DIMENSIONS


H600 + Auto-Shim Spreader



H600 + PM10 Pin-On Axle



H600 + V10 Booster



For more information
 Call us at 1-888-227-2638
 Email us at sales@brandt.ca
 Or visit us at brandt.ca/trailers

© Brandt Industries Ltd. All rights reserved. The Brandt name and logo are trademarks of Brandt Industries Ltd., used under license. All product information and specifications are subject to change without notification. Printed in Canada. Revised 12/2023-CU

