

LEAD
THE
FIELD.

DXR GrainCarts



Speed Up Your Harvest.

Brandt's dual-auger DXR-Series grain carts deliver full capacity with any product, under any conditions to meet the rigorous demands of a fast-paced harvest. They are available in 1150, 1500, and 2000-bushel sizes to suit your operational needs with minimal downtime.

① Quick Turnaround

DXR grain carts deliver grain to your trucks quickly:

- The belt-driven 20" floor auger and heavy-duty 22" vertical auger enable unload speeds of up to 800 bu/min.
- The vertical auger has an industry-leading range of motion in height adjustment with over 7 ft. of travel ensuring fast, worry-free positioning.
- The discharge spout automatically rotates to a safe transport position so you can spend less time at the truck and back to your combine quicker.

② Total Cleanout

Longer, narrower tank design delivers fast complete tank cleanout on every cycle:

- Steep, ledge-free tanks with round cross-supports ensure there are no hang-up points to prevent grain flow.
- Full-length cleanout doors make crop switching or end-of-season maintenance simple and fast.
- Loading-side heights as low as 11' guarantee safe and easy combine unloading on any terrain.

③ Accurate Load Management

Load your truck at the correct weight while keeping accurate track of grain inventory:

- A five-point scale system ensures your trucks are loaded to the exact weight you need.
- Digi-Star Scale data management system allows you to keep track of your harvest; including GPS, moisture levels, and wifi modules for comprehensive data tracking.
- Autolog technology automatically captures detailed data the minute you engage the tractor's PTO. And, Auto Unload automatically stops when you hit a pre-set load to ensure you don't overfill the truck.

Powerful Value. **Delivered.**

Brandt

DXR GRAINCARTS

SPECIFICATIONS

	1122DXR			1522DXR		2022DXR	
Performance							
Capacity (bushels)	1,150			1,500		2,000	
Unload Speed (bu/min)	800			800		800	
Minimum Horsepower	225+			300+		400+	
Auger Diameter	20" Horizontal into 22" Vertical			20" Horizontal into 22" Vertical		20" Horizontal into 22" Vertical	
Flighting	1/2" Extended Life			1/2" Extended Life		1/2" Extended Life	
Adjustable Discharge Travel	91°			91°		91°	
Undercarriage	High Flotation	Extreme Flotation	Tracks	Tandem	Tracks	Tandem	Tracks
Tire/Track Size	LSW1100/45R46	IF1250/50R32	136" x 36"	900/60R32	147" x 36"	IF900/60R32 CFO	170" x 36"
Tire Load Index	195	201	n/a	185	n/a	188-A8	n/a
Axle Spindle Diameter	5.5"	5.5"	5.5"	3.75"	5.5"	4.5"	5.5"
Loaded Surface Ground Pressure (psi)	37	33	13	47	14	41	15
Weight							
Empty (lb)	19,500	20,000	29,500	29,000	31,500	30,780	33,700
Tongue - Empty (lb)	3,600	3,600	3,600	3,900	3,900	4,340	4,340
Tongue - Full (lb)	5,200	5,200	5,200	5,700	5,700	5,175	5,175
Dimensions							
Height Hitch	1'4" - 1'9"	1'4" - 1'9"	1'4" - 1'9"	1'4" - 1'9"	1'4" - 1'9"	1'4" - 1'9"	1'4" - 1'9"
Axle to Tongue Length	18' 3"	18' 3"	18' 3"	21'	21'	22' 4"	22' 4"
Overall Length	27' 7"	27' 7"	27' 7"	33'	33'	36'	36'
Hopper Length	18' 4"	18' 4"	18' 4"	24'	24'	27' 5"	27' 5"
Discharge Height	9'10" - 16'11"	9'10" - 16'11"	9'10" - 16'11"	9'5" - 16'6"	9'5" - 16'6"	9'9" - 16'10"	9'9" - 16'10"
Auger Reach	5'3" - 9'3"	5'3" - 9'3"	5'3" - 9'3"	5'3" - 9'3"	5'3" - 9'3"	5'3" - 9'3"	5'3" - 9'3"
Overall Width	13' 2"	13' 2"	13' 2"	12' 9"	12' 9"	13' 11"	13' 11"
Minimum Hopper Height	11' 5"	11' 2"	11'	11'	11'	11' 6"	11' 6"
Loading Side Height	11' 5"	11' 2"	11'	11'	11'	11' 6"	11' 6"
Transport Height	12' 11"	12' 8"	12' 6"	12' 6"	12' 6"	12' 6"	12' 6"
Ground Clearance	1' 6"	1' 2"	1' 2"	10"	1' 2"	1' 2"	1' 2"
Wheel Inside Width	5' 11"	5' 5"	6' 2"	7' 6"	6' 2"	7' 5"	6' 10"
Wheel Track Width	9' 6"	9' 6"	9' 2"	10' 5"	9' 2"	10' 6"	9' 10"
Wheel Outside Width	13' 2"	13' 8"	12' 2"	13' 3"	12' 2"	13' 7"	12' 10"

OPTIONS

Hydraulic brakes

Camera kit

Enhanced lighting kit

Electric tarp

Joystick control kit

Undercarriage:

- Extreme flotation tires
- Steerable tandem axles
- Brandt's purpose-built track system

For more information
 Call us at 1-866-4-BRANDT
 Email us at agriculture@brandt.ca
 Or visit us at www.brandt.ca

Brandt Agricultural Products
 PO Box 317, 13th Avenue & Pinkie Road,
 Regina, SK, Canada
 S4P 3A1

