

UBE518 UBE720

LOW-PROFILE FLATBED TRAILERS



2 WARRANTY

Unmatched 2-Year Bumper-to-Bumper Warranty on all components. 5-Year Structural Warranty. Ask us for details.

Trailer details may differ from image

Flat Out Results.

The Work Ready™ Brandt UBE518 and UBE720 low-profile flatbed trailers deliver superior capacity to get your equipment where it's going, every single day. These rugged models work as hard as you do, while taking all the punishment you can dish out.

1 Built to Last

Brandt trailers are purpose-built to maximize your productivity from dusk till dawn until the job gets done:

- A unified-frame design integrates the frame and deck into a single robust structure to minimize weak points and stress concentrations.
- Designed for optimal balancing with construction equipment, allowing for the most stable and secure load platform in the industry.
- Reliable design and long-lasting components reduce total cost of ownership.

2 Easier to Operate

These trailers are designed for fast, effortless loading so you can start working sooner:

- Bolt-on key components are easily replaceable for fast maintenance, making this a fully serviceable design for maximum uptime.
- Three ramp configurations accommodate equipment with ease, ensuring superior versatility.
- Standard tool tray located in the tongue of the trailer provides convenient storage and access to tools.

Safer

Safety is critical on the jobsite, so these models are designed with key features to maximize operator protection:

- Dependable 5200 lb axles (UBE518) and 7000 lb axles (UBE720) are standard on all configurations to ensure positive hitch weight distribution and overall stability when hauling concentrated heavy payloads.
- Standard lower sidestep and bi-fold, fullwidth spring-assisted ramps with a knee support allow operators to work safely.
- Premium decking provides better traction for the operator in wet and frozen conditions and reduces wear over time.



LOW-PROFILE FLATBED TRAILER TECHNICAL SPECIFICATIONS

| QUICK REFERENCE CHART | UBE518 Low-Profile Flatbed | | UBE720 Low-Profile Flatbed | | | | |
|--|---------------------------------------|---------------------------|---|-----------------------------|---|--------------|--|
| Base Unit Key Specifications | PERFORMANCE | PERFORMANCE GALVANIZED | PERF | PERF GALV | PREMIUM | PREM GALV | |
| RELIABILITY - RATED CAPACITY | | | | | | | |
| GVWR (lb) | 99 | 00 | | 14, | 900 | | |
| Rated Payload (lb) | 7050 7000 | | 11,600 | 11,600 11,550 11,250 11,200 | | | |
| Tongue Weight (lb) | 12: | 50 | | 18 | 60 | | |
| Suspension | Torsion - Bolt On | | | Torsion - Bolt On | | | |
| Axle Rating (lb) | 2 x 5200 | | 2×7000 | | | | |
| DURABILITY - STRUCTURE | | | | | | | |
| HSS Mainframe Size (in) | 6 | j | | | 3 | | |
| Premium Fir Decking | 0 | • | 0 | • | • | • | |
| Pressure Treated Spruce/Pine Decking | 0 | | 0 | | | | |
| Surface Finish | Powder Top Coat, Polyester JD Grey | Galvanized | Powder Top Coat, Polyester JD Grey | Galvanized | Powder Top Coat, Polyester JD Grey | Galvanize | |
| DIMENSIONS | | | | | | | |
| Total Length (ft) | 24.7 | | 20 | 26.9 | | 7.2 | |
| Fixed Deck Length (ft) | 16 | | 18 | | | | |
| Dovetail Length (ft) | 2 | | 2 | | | | |
| Deck Width (in) – inside fender to fender | 82 | | 82 | | | | |
| Deck Height (in) | 2 | 22 | | | | | |
| INCLUDED EQUIPMENT | | | | | | | |
| Pull Type | Bumper | | | Bumper | | | |
| Jackleg Wind Type – top or side | Тор | | | Side | | | |
| Jackleg Speeds | Single | | Single | | | | |
| Jackleg Lift Capacity (lb) | 7000 | | 10,000 | | | | |
| Steel Tread Plate Fenders – bolt on | • | | • | | | | |
| Black Steel Wheels | • | | | • | | | |
| Tire Size | ST225/75R15 LRE | | ST235/80R16 LRE | | | | |
| Premium Radial 10 ply Tires – speed rated to 120 kph | • | • | | | | | |
| EASY TO OPERATE - SAFETY & CONV | ENIENCE FEATURES | | | | | | |
| Spring Assist Flip Up Ramps – 24 x 60" | 0 | • | (|) | | | |
| Spring Assist Full Width Bi-Folding Ramps – 40 x 60" | | | | | | | |
| Spring Assist Full Width Expanded Metal Mesh, Flip-Up w/ Knee Support Ramps – 82 x 60" | 0 | | C |) | | | |
| Steel Tread Plate Fenders – bolt on | | | | | | | |
| Premium Protected Wiring | | | | | | | |
| Breakaway Switch – includes LED test lights, battery & charger | | | | | | | |
| Integral Footholds | | | | | | | |
| Tier 1 LED Lighting System | | | | | | | |
| Forward Self-Adjusting Brakes | | | | | | | |
| E-Z Lube Grease Axle Bearings | • | | • | | | | |
| Load Bearing Toolbox | C |) | (|) | | | |
| ACCESSORIES | | | | | | | |
| Coupler Lock | C |) | | (| | | |
| Wheel Locks | C |) | | (| | | |